

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec Cor 1 & 2; 35 & 36, T26-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set Post, cor. to Secs. 35, 36, 1 & 2, from which  
A Y.Oak, 20" dia. bears S.83½°W., 109 lks. dist.  
A Y.Oak, 12" dia. bears N.62°W., 74 lks. dist.  
A Y.Oak, 10" dia. bears N.7½°W., 157 lks. dist.  
No trees east of line near.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone; Mike  
Darby; - March 31, 1964 - C.S. 49/125-101  
-----

Found - ¾" Iron rod at approx. corner location. (source?)  
All 3 orig. BTs found. bearings & distances  
according to gov't notes as follows:  
20" B.Oak, now 52", S.83½°W., 109 lks., opened  
prev., center rotted.  
12" B.Oak, now 34", N.62°W., 74 lks. shows good scar  
10" B.Oak, now 26", N.7½°W., 157 lks. shows very  
good scar.

Bearings fit very closely, but distances vary from 1.5 ft. to  
8 ft. from record distances. Since it is impossible to find  
any one point which will fit distances given, I decide to  
accept rod found as corner.

Set -Brass cap at cor. mkd. County Surveyors S35|S36 T26S R5W  
Office 1964 S 2|S 1 T27S

New BTs - 12" B.Oak N.11°E., 10.3 ft. mkd. T26S R5W S36 CS BT.  
10" B.Oak S.84°E., 21.6 ft. mkd. T27S R5W S1 CS BT.  
9" B.Oak S.56°W., 24.3 ft. mkd. T27S R5W S2 CS BT.  
Old BT. 26" B.Oak N.8°W., 102.1 ft. still in good  
condition, not rescribed.

Fence Corner - fences north & east, bear South 19.5 ft.

Doug. Co. Surveyors Office - Gary L. Langlitz; Karen Cheney  
June 9, 1977 - C.S. 59/34-34  
-----

Found - 1" I.P. with 1964 DCSO BC attached & mkd. as  
described by Godfrey, extending 12" above  
ground with 3/4" R. Rod alongside.  
An orig. 20" now 52" B.Oak alive & prev. opened,  
no markings visible, bears S.82°W., 70.0 ft.  
(Rec. S.83½°W., 71.9 ft.)  
An orig. 12" now 34" B.Oak, alive with faint scar  
CONT. NEXT PAGE

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. 1 & 2; & 35, 36 of T26-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

cont.                    visible, bears N.65°W., 50.4 ft. (Rec. N.62°W., 48.8 ft.)  
                          An orig. 10" now 31" B.Oak, alive with good scar visible, bears N.7½°W., 102.9 ft. (Rec. N.7½°W., 103.6 ft.) and (Rec. per Godfrey, N.8°W. 102.1 ft.)  
                          A 12" now 12" B.Oak, alive with healed single blaze bears N.14½°E., 10.3 ft. (Rec. N.11°E., 10.3)  
                          A 10" now 13" B.Oak bears S.81½°E., 21.1 ft. alive with healed double blaze. (Rec. S.84°E., 21.6')  
                          The SW BT is gone.  
                          Condition report only, no monument set or new accessories.  
                          A corner of fences running N & S bears South 19.5 ft.

Found OK by K. DeGroot, June 2000 - M132-38  
Fd. Ok by K.DeGroot, 7/2005 - M146-23