

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Elder &amp; Gile, Contract #31 dated, April, 1853 ----- Set ¼ Sec. post, from which     A Y. Oak 18" dia. bears N.53½°E., 136 lks. dist.     A Y. Oak 15" dia. bears S.8°W., 172 lks. dist.</p>
<p>Ben B. Irving, County Surveyor - For California Oregon Power Co. - April, 1953 - C.S. 45/150 ----- Set - 1" brass cap from O.B.T. New BTs - 20" W. Oak S.82°W., 68.9 ft.           10" W. Oak N.16°30'E., 63.7 ft.</p>
<p>Found Brass cap &amp; accessories. Donald Bentz, Dec. 1992, Land Partition, 1993-0008.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/18/93 -C.S. File 64/50-10 ----- Found - A 2½" dia., DCSO Brass Cap on a 1½" O.D. Iron Pipe           protruding 2" above ground. (1953 BBI)           20' now 15" dia., down and rotted W. Oak with a           rotted double blaze, no scribing visible, bears           S.82°W., 68.9' to root hole. (Agrees with rec.)           1953 BBI.           10" now 12" dia., W.Oak with a fully healed double           blaze, bears N.21°E., 63.7' (Rec. N.16½°E.,           63.7') 1953 BBI.           Both Orig. BTs now gone. New BTs - 13" dia., W.Oak double blazed and scribed "¼ S25 CS           BT", bears S.79°W., 61.8'.           5" dia., D.Fir, double blazed and scribed "¼ S24 CS           BT", bears N.65°W., 34.5'.           9' dia., D.Fir, double blazed and scribed "¼ S25 CS           BT", bears S.80°E., 26.4'.           See sketch in file. Note - Corner located at the intersection of a 4 way fence           corner.</p>
<p>Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 3/17/2008 - C.S. File 67/25-34 ----- Fd. DCSO BC &amp; 3 live BTs &amp; 1 dead BT.</p>