

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which A Y.Oak, 12" dia. bears N.75½°E., 41 lks. dist. A Y.Oak, 8" dia. bears S.41¼°E., 71 lks. dist.</p>
<p>Glenn S. Baughman - For Snowbird Stone - Aug. 1970 - Filed Jan. 19, 1971 - M 41 - 7 ----- Set ¼ Corner by proportionate measurement. Set - Brass cap stamped ¼ Cor. Secs. 12 & 13. Scribed - 10" B.Oak bears N.63°W., 63.0 ft. 9" Pine bears S.78°W., 68.2 ft.</p>
<p>Found OK per Raleigh, Dec. 1988 - RM 3 - 70 A&B</p>
<p>Douglas Co. Surveyors Office - Randall Smith, Stephen Flause; May 3, 1994 - C.S. File 64/51-15 ----- Found - 2½" dia. Brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground. (1971 Baughman) 10" now 15" dia. B.Oak with a fully healed double blaze, bears N.59°W., 62.1 ft. (rec. N.63°W., 63.0 ft. distance is a slope measurement) 1970. 9" now 17" dia. Pine with a fully healed double blaze, bears S.78°W., 68.2 ft. (1970). New - 11" dia. Madrone bark scribed "1/4 S13 CS BT" bears S.29°E., 18.3 ft. 17" dia. B.Oak double blazed & scribed "¼ S13 CS BT" bears S.4½°E., 51.0 ft. Note - Corner lies on an east-west fence line.</p>
<p>Fd. Ok by K.DeGroot, 7/2005 - M146-23</p>
<p> </p>