

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor 25 & 36; 30, 31 T27-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, Contract #1 dated May, 1851  
-----

Set Post cor. of secs. 25, 30, 31 & 36, from which  
A B.Oak 16" dia. bears N.46°30'E., 37 lks. dist.  
A B.Oak 12" dia. bears S.45°E., 4 lks. dist.  
A B.Oak 11" dia. bears S.37½°W., 45 lks. dist.  
A B.Oak 10" dia. bears N.59°W., 79 lks. dist.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A.  
Bilow - Jan. 23, 1959 - C.S. 49/130-12  
-----

Found - Orig. 11" now 20" B.Oak, I open & find good  
scribing "S36", S.37½°W., 29.7 ft.  
Orig. 10" now 24" B.Oak, N.59°W., 52.1 ft., should  
be 58.7 ft. shows scar, I do not open.  
Stump holes that check orig. NE & SE BTs.

Set - Brass cap at cor. mkd. County Surveyor's Office 1959  
S25|S30  
R5W S36|S31 T27S

New BTs - 11" W.Oak bears N.0½°W., 56.0 ft. scribed S25 T27S  
R5W CS BT.  
6" W.Oak bears N.75°W., 33.4 ft. scribed S25 CS BT.  
Rescribe orig., now 20" B.Oak S.37½°W., 29.7 ft. S36  
T27S R5W CS BT.  
No trees near to SE and NE.

Found OK April 18, 1980 M79-35

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 4/26/2007 - C.S. File 67/21-33  
-----

Found - 2½" dia., brass cap properly marked on 1¼" O.D. iron  
pipe, projects 15" above ground. Iron pipe is  
bent easterly (downhill) approx. 0.6 ft.  
Orig. 11", now 41" dia., B.Oak, healed blaze faint,  
bears S.37½°W., 29.7 ft. (agrees w/rec) OBT  
6" now 17" dia., W.Oak, no blaze visible, bears  
N.75°W., 33.4 ft. (agrees w/rec.) 1959 BT  
Orig. 10" now 31" dia., B.Oak, no blaze visible,  
bears N.56°W., 55.9 ft. measures 58.7 ft. on  
slope (18°) (Rec. N.59°W., 52.1 ft.)  
11" now 25" dia., W.Oak, no blaze visible, bears  
N.0½°W., 56.0 ft. (agrees w/rec.) 1959 BT.

New - BC/IP was referenced out, removed, IP straightened  
out, and replaced at referenced position. Brass  
cap projects 3" above ground.

continued next page

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; 30, 31 T27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Corner lies on East facing slope approx 200 ft. east of ridge top. Open hillside pasture to NE & SE quadrants.  
Compass decl. 16¼°E.

Fd. OK by Kris DeGroot, 6/2009 - 2009-0034A&B