

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 25; & 30 of T27-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, Contract #1 dated May, 1851

-----  
Set ¼ sec. post, from which  
    A B.Oak 12" dia. bears S.10°E., 50 lks. dist.  
    A B.Oak, 12" dia. bears S.20°W., 125. lks. dist.

James W. Byron, Deputy - Milo Godfrey; S.A. Bilow  
Jan. 23, 1959 - C.S. 49/130-14

-----  
Found - Orig. 12" now 24" B.Oak S.20°W., 82.5 ft., I  
        open & find good scribing "S".  
        No trace of original SE BT found.  
Set - Brass cap at cor. mkd. County Surveyor's Office  
            ¼ S 25 | S 30  
            R5W       R4W  
                    1959

New BTs - 14" R.Fir bears N.21°E., 19.5 ft. scribed ¼ S30 CSBT  
          11" R.Fir bears S.72°W., 24.7 ft. scribed ¼ S25 CSBT  
Note - N-S fence 4 ft. west.

Doug. County Surveyors Office - Randall Smith; Stephen Flauser  
April 27, 1993 - C.S. File 64/43-20

-----  
Found - 2½" dia. 1959 DCS0 brass cap on 1½" O.D. I.P. pro-  
        truding 12" above ground  
        12" now 26" dia. 3 ft high B.Oak stump, possible  
        healed lower blaze, fallen Oak tree along West  
        side, re-opened previously opened blaze, find  
        blaze, axe marks and illegible scribing.  
        Stump bears S.20°W., 79.8 ft. (Rec. S.20°W.,  
        82.5 ft.) Area of cor. is on a steep North  
        slope, which may account for dist. problem.  
        (Orig. BT.)  
        11" now 22" dia. D.Fir with a fully healed double  
        blaze bears S.72°W., 24.0 ft. (Rec. S.72°W.,  
        24.7 ft. 1959 BT.)  
        14" now 18" dia. 1½ ft. high D.Fir stump, I opened  
        a lower blaze and find scribe marks "BT", stump  
        bears N.21°E., 18.7 ft. (Rec. N.21°E., 19.5  
        ft.) 1959 BT.  
New BTs - 18" D.Fir double blazed and scribed "¼ S25 CS BT"  
          bears N.47½°W., 34.3 ft

(Cont. Next Page)

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 25; S. 30 of T. 27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

17" Madrone, bark scribed "¼ S30 CS BT" bears  
S.64½°E., 19.7 ft.  
9" D.Fir double blazed and scribed "¼ S30 CS BT"  
bears N.59°E., 30.1 ft.  
Corner lies 4 ft. East of a North-South fence line on a steep  
North slope.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -  
3/17/2008 - C.S. File 67/25-34  
-----  
Fd. BC & 3 live BTs & 2 BT stumps