

TOWNSHIP 27 RANGE 05 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12; & S. 7, T27-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, Contract #1 dated May, 1851  
-----

Set ¼ sec. post, from which

A Willow, 11" dia. bears S.22°E., 137 lks. dist.

A Willow, 12" dia. bears S.26°E., 125 lks. dist.

Glenn S. Baughman - For: Snowbird Stone - Aug. 1970

Filed Jan. 19, 1971 - M 41 - 7  
-----

Set ¼ cor. by proportional measurement.

Set - Brass cap stamped.

Scribed - 36" Alder bears S.33°W., 243.2 ft.

11" W.Oak bears N.68°E., 350.5 ft.

Glenn Baughman - For: Kenneth Miller - Jan. 1984 - M 95-73  
-----

Found - 1¼" I.P. with brass cap attached.

24" double Ash (Rec. Alder) S.36°41'W., 243.2 ft.  
scribe visible. (Rec. S.33°W., 243.2 ft.)

12" W.Oak stump N.67°05'E., 352.1 ft. (Rec. N.68°E.  
350.5 ft.)

Set - R.P. spike in PP & L Pole No. "6/99 R", S.34°05'E.,  
142.1 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/24/94 - C.S. File 64/50-16  
-----

Found - 2½" dia. brass cap on 1¼" O.D. iron pipe protruding  
3" above ground. (1970)

24" now 41" dia., double trunked Ash with a  
partially healed double blaze on 24" dia.,  
Northerly trunk "¼ S12 BT" root crown bears  
S.35¼°W. 243.2' (Rec. S.36°41'W. 243.2') 1970.

NE Oak now gone (1970)

R.P. spike in PP&L pole No. 6/99 R is gone (1984)  
replacement pole marked "91 DFPA 60 HI 85"  
bears S.35½°E., 143.1'.

New Accessories -

5'x13'x2' high concrete water trough, SE corner  
bears N.12°E., 88.4'.

(Cont. Next Page)

