

TOWNSHIP 27 RANGE 06E POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #473, dated June 5, 1883 (DCSO Records Vol. 24 Page(s) 10169)

Set post 44x4" sqr., 12" in the ground for ¼ sec. cor., marked ¼ S on N face, from which
 A pine, 6" dia., bears S.23°E., 15 lks., mkd: ¼ S BT.
 A pine, 7" dia., bears S.20°W., 14 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Dennis Gaylord, USFS & DCSO Deputy - Witness: B. Dorsey - May 1980 - C.S. File 61/9

Set - 2" Iron pipe 36" long with a 2½" BRASS CAP attached properly marked.
 An 11" Lodgepole Pine bears N.59°30'E., 36.6 ft. scribed "¼ S29 CS BT" on double blazes.
 An 11" Shasta Red Fir bears S.26°30'E., 62.2 ft. scribed "¼ S32 CS BT" on double blazes.
Note- A diligent search of the area did not reveal any original corner evidence. The corner was reset by proportional measurement.