

PRIMARY CORNER DESCRIPTION SW Cor. McKinney DLC #50

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April 1854  
-----  
Set Post on side hill deposited stone 6 x 5. Raised mound with trench as per instructions.

---

Ben B. Irving - Wit. N.E. Richardson; Cliff Mabley -  
April 1, 1928 - Survey of Co. Rd. #13 - "Old" Ren. Vol. 1  
-----  
Found 4 x 5 rock as called for in original notes. Blazed and scribed BTs as follows:  
    Black Oak 8" dia. bears N.43°E., 62 lks. mkd. S.W.  
        Cl. 50 C.S. B.T.  
    White Oak 8" dia. bears N.70°E., 66 lks. mkd. S. W.  
        Cl. 50 C.S. B.T.

---

Shaner Engineering - June 14, 1993 - M 112-75 & C.S. 63/153-54  
-----  
Found rock, top is 4"x 5", buried in ground (est. Length 18") & from which a rock:  
    16" W. Oak BT stump, badly rotten with reverse scribes showing near stump center, bears N43°E. 40.9 ft. (was originally 8" Black Oak in 1928).  
    14" W. Oak BT, face shows axe mark but is now overgrown (I did not open), bears N70°E., 43.6 ft. ( was 8" W. Oak in 1928).  
I set 2 each steel fence posts, one at due west 1 ft. and one at due north 1 ft.  
Also from corner rock:  
    10" W. Oak BT, I scribed "SWC CL50 BT", bears N48°E, 45.2 ft.  
Corner is N.45°W, approx. 300 ft. from the Denzer residence at 641 San Souci Dr.

---

Douglas County Surveyors Office - Randy W. Smith & Stephen Flause - 8/31/93 - C.S. 64/46-11  
-----  
Found - A sand stone monument protruding 3" above ground. Top measures 6"x5". Orig. stone.  
    8" now 16" dia. 3½' high rotted oak stump, with illegible reverse scribing, bears N.43°E., 40.9 ft. (agrees with record) 1928 BBI.  
    8" now 14" dia. W. Oak with a fully healed single blaze, bears N.70°E., 42.9 ft. (rec. N.70°E., 43.6 distance is a slope measurement) 1928 BBI.  
    10" dia., W. Oak with a recent single blaze scribing visible "SWC CL50 BT" bears N.45°E., 45.2 ft (rec. N.48°E., 45.2 ft) 1993 Shaner. Cont.

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 050050

PRIMARY CORNER DESCRIPTION SW Cor. McKinney DLC #50

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Monuments Set:

Stone referenced, fd. unmarked and measured 15" long when removed a 2 3/8" dia. by 32" long iron pipe is set at referenced position, BC/IP protrude 9" above ground.

Corner stone is set along North edge of BC/IP, protruding 4" above ground. Douglas County Surveyors

T 27 S  
R | DLC  
6 | 50  
W SW Cor  
1993

New BTs- 10" dia. B. Oak double blazed and scribed "SW DLC 50 CS BT", bears N.25½°E., 33.6 ft.

6" dia. W. Oak double blaze and scribed "SW DLC 50 CS BT" bears N.55½°E., 31.2 ft.

Two fence post set by Shaner fd. North 1 ft. & West 1 ft.

Found OK by Shaner, Sept. 1996 - M 125-62 A & B; Corner report C.S. 65/8-7B.