

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 056010

PRIMARY CORNER DESCRIPTION N.E. Cor. Huntley DLC #56

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set Post from which:
 A W.Oak 15" dia. bears S.43°W., 657 lks.
 Raised mound with trench as per instructions.

F.C. Frear, Roadmaster - P.D. Wolford; Dick Guthrie, Wit.
Jan. 9, 1923 - Reff. may be in Co. Road Notes, Frear Co.Rd.
#6 - See "old" ren. Vol. 1 - Also see Vol. 4 Pg. 53

Renewed from old stake set by State Highway Engineers and
later permanently established by auto axle set in 15" x 15"
concrete on center line with Edenbower Pavement.

James W. Byron; M. Godfrey; S. Bilow - January 3, 1958
C.S. File 49/55-1

Found - 1" Axle set in concrete.
Set - 1" Pipe with brass cap stamped "County Surveyor's
 office, 1958, T.27 S., R.6 W., N.E. Corner
 D. L. C. 56".
See sketch in File for exact location of brass cap.

Found by Ore. St. Hwy. Dept. See L - 7
Found OK Jan. 1990, M. Heimbürger, M 101 - 71

FD OK by Donald Bentz - Vol. 18 Pg. 42 - Dec. 1994