

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 056020

PRIMARY CORNER DESCRIPTION NW Cor. Huntley DLC #56

Alias <u>065050</u>	Description <u>Int. I Jones DLC #65</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set Post in prairie, deposited quartz stone 8 x 4.
Raised mound with trench as per instructions.

F.C. Frear, Roadmaster - P. D. Wolford; Dick Guthrie, Wit.
Jan. 9, 1923 - Ref. may be in Co. Road Notes. Frear, Co.
Road #6 - See "old" Ren. Vol. 1 Pg. 92.

Renewed from old pipe, set by F.C. Frear as corner.
Set pipe for corner in edge of pavement, in a projection
at side of pavement. Set in 6" concrete on Edenbower
Pavement by Davis house.

A. R. Evans, Surveyor - R. G. Irving, wit. - Aug. 1, 1949
C. S. File 43/55

Replaced from property corners.
Set - Brass cap in 24"x24"x20" concrete on edge of pave-
ment of Garden Valley Road. Brass cap on 2½"
I.P. mkd. County Surveyors Office, DLC 56-
DLC 65. From Which:
Brass cap marking the NE corner of U.S. Vet's Adm.
property bears South 21.18 ft.
2" pipe marking the Initial Point of Eden Heights
Extension as platted and filed in the office
of the County Clerk.
(Corner found, See M 7 - 42)

James W. Byron, Deputy - For: Tidewater Oil Co. - M. Godfrey
& C. Putnam - Sept. 17, 1959 - C.S. 49/184 & M 11 - 36

Set PK Nail for Corner. Found Highway monument Witness Cor.
Chisled + in concrete curb. o Fd. Hwy.Mon. W.C.
 | ← 33 ft.
 o-----
 | ← 26.55 ft.
 + chiseled + on conc. curb
 |

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 056020

PRIMARY CORNER DESCRIPTION NW Cor. DLC #56

Alias 065050 Description Int. I, Jones DLC #65
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors office - Larry E. Monrean, Deputy Randall Smith; S.J. Flause - Aug. 22, 1984 - C.S. 62/22

Found - Upon examination of the site on Aug. 22, 1984, we located a ¾" x 24" iron pipe set 23" below the asphalt surface which we later accepted as the corner location.

Also found was a ¾" x 20" iron bolt 10" below the asphalt surface, bears N.02°51'09"W., 0.83 ft. from found iron pipe.

Along with the above noted monuments, monuments from recorded surveys were tied by survey. Record bearings & distances were used to determine the most probable position. (For procedures and sketch, see C.S. file 62/22).

Set - We replace the ¾" x 24" I.P. with a 3" dia. brass cap mkd.: "T 27 S R 6 W" DLC

65 | DLC
56
1984

The cap is set in a 5½" x 21" iron water valve box filled with concrete. Cap is 5" below asphalt surface.

Reference Monuments:

The southwest corner Lot 1, Bl. 7, Eden Heights Extension. A ¾" iron rod bears N.76°09'24"E., 148.92 ft.

The northeast corner of Lot 1, Bl. 1 Mulholland Meadows. A 1½" iron pipe bears N.04°18'46"E., 184.85 ft.

The northeast corner of parcel per C.S. 51/54. An iron rod & plastic cap bears S.77°06'50"E., 154.22 Ft.

Found OK by G. Baughman - April 1993 - M 117-12

Fd. OK by C. Blevins, 2/1999 - ~~M133-75-A-L~~ ST HWY I5-006 C

Fd. Ok by E Hibbs, 7/2023 - ST HWY I5-037B