

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 059030

PRIMARY CORNER DESCRIPTION SW Cor. Hardy DLC #59

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 ----- Set post in prairie, deposited stone 6 x 5. Raised mound with trench as per instructions.</p>
<p>W.F. Briggs, Surveyor - Wit: C.W. Hatfield; G. Scott - FB 95 Pg. 90 and Vol. 1 Pg. 246 - April, 1893 ----- Set a 12" x 4" x 4" rock for the corner with post alongside marked C 59, C. S. No trees near.</p>
<p>Found steel shaft, no record. June, 1984, R. Ware - M90-57 Fd. ok by D. Edwards 10/2004 2004-0062 A&B</p>
<p>DCSO-GIS Corner visitation - 8/3/2004 - Typed: 1/28/2011 - C.S. File 67/33-1 ----- Monument - 1 7/8" Comment - (needs) rehab</p>
<p>Ken Hoffine - For: TBT Properties LLC - 7/2016 - C.S. 65/92-12 ----- Found - 1 7/8" steel shaft as per M90-57 Set - 5/8"x40" iron rod with orange plastic cap mkd: LONE ROCK TIMBER LS2291 in fence line, bears N.89³/₄°E., 63.5' 5/8"x40" iron rod with orange plastic cap mkd: LONE ROCK TIMBER LS2291 in fence line, bears N.1¹/₄°W., 81.1' Unable to located orig. stone beside steel shaft. Corner lies in open field at junction of three way fence approx. 2 ft. north of edge of gravel driveway, 0.1 ft. above ground level.</p>
<p> </p>