

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 064030

PRIMARY CORNER DESCRIPTION SW Cor. LaPoint DLC #64

Alias 100544 Description On line between Sec. 7 & S12 T27-7
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854 -
(DCSO DLC records Pg. 432)

Set a post for SW cor. of C 64 from which
A B.Oak 10" dia., bears N.60°E., 30 lks.
A B.Oak 8" dia., bears N.73°W., 39 lks.
A Laurel 36" dia., bears S.36°E., 25 lks.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 10/28/2002 - C.S. File 66/34-47

Found - 10" now 28" dia., B.Oak hollowed out on back side,
find old rotted blaze and axe mark reverse
scribing found "S and a line" bears N.60°E., 19.8
ft., to blaze (OBT) 20.2 ft. to center.

Orig. NW BT gone.

36" Laurel now 56" dia., triple trunked Madrone we
open & find good illegible scribe marks, bears
S.36°E., 16.5 ft. to blaze (OBT) 18.2 ft. to
center of root crown.

Set - A 2½" dia., brass cap on a 1½" O.D. by 32" long iron
pipe at a position determined from OBTs.
Protrudes 5" out of ground, mkd:

DOUGLAS COUNTY SURVEYORS OFFICE

T27S
| DLC R
| 64 6
| SW W
2002

Corner lies 4 ft. East of a N-S fence line.

31" dia., B.Oak double blazed & scribed "SW DLC 64
CS BT" bears N.13½°W., 40.6 ft.

19" dia., D.Fir double blazed & scribed "SW DLC 64
CS BT" bears N.84°E., 20.2 ft.

14" dia., D.Fir double blazed & scribed "SW DLC 64
CS BT" bears S.44°W., 29.3 ft.

Compass decl. 17½°E.