

PRIMARY CORNER DESCRIPTION S.E. Cor. LaPoint DLC #64

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint - Contract #28 dated April, 1854

-----  
Set post for S E corner of C 64, from which  
Black Oak 30" dia. bears S.86°E., 659 lks.  
No other tree convenient.

-----  
G.R. Lecklider, Engineer - For: C.W. Hagen & Bessie Smith  
September, 1958 - C.S. File 42/393 & M 12 - 67

-----  
Found - 3 stones leaning against each other, in dense  
growth of rose bushes, as if they had been  
placed around a post at one time. These were  
only stones in the immediate area from which  
A 64" W.Oak bears S.84°E., 380.3 ft., record,  
S.86°E. 434.94 ft. which has an old catface  
on the West side, I open, no scribe visible.

I accepted the stones as the SE corner of DLC #64 because they  
fit the overall conditions better in both latitude and  
departure than a point set record bearing and distance from  
the 64" W. Oak.

Set - A 5/8" x 40" Rod at this point and surrounded with  
the 3 stones. From which  
24" D.Fir bears S.79°W., 27.5 ft.  
22" D.Fir bears South, 16,0 ft. and both marked  
"DLC 64 BT".

-----  
Found OK March, 1977, H.L. Northcraft - M 63 - 72

-----  
Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - 4/3/96 - C.S. 64/66-12

-----  
Mon. Fd.- 5/8" I.R. protruding 5" above 3 stones (1958)  
BT's Fd.- 30" Black oak, now 48" dia. 12' high rotted oak snag  
showing an unhealed previously opened blaze,  
no scribing found, bears S.86°E., 388.4'.  
24" now 33" dia. down D.Fir, with a fully healed  
blaze, root hole, bears S.79°W., 17.5'.  
22" now 36" dia. 2' high D.Fir stump, with a fully  
healed blaze, bears south 16'.

Mon. Set- ground soft with standing water, did not set a BC/IP  
New BT's- 17" pine, double blazed and scribed "SE DLC 64 CS  
BT", bears N.49½°W., 38.6'.  
15" D.Fir, double blazed and scribed "SE DLC 64 CS  
BT", bears S.67°W., 95.9'.

(Cont. Next Page)

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 064040

PRIMARY CORNER DESCRIPTION S.E. Cor. LaPoint DLC #64

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" D.Fir, double blazed and scribed "SE DLC 64 CS BT", bears S.83°E., 67.5'. 3" D.Fir, double blazed and scribed "X BT", bears N.20½°E., 17.9'.
DCSO-GIS Corner visitation - 8/3/2004 - Typed: 1/28/2011 - C.S. File 67/33-1  ----- Monument - 5/8" rebar Comment - (needs) rehab - 8; stones gone, rebar bent.
2