

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. For 30 & 31; 25 & 36, T.27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 25, 30, 31 and 36. Drove charred stake and raised mound with trench and pits, as per instructions.

Roger Gee, For: E. G. Ziegler Oct. 1967, M 33-48

Set - 1 1/4" Iron rod by proportionate measurement.
Note - Wit. Corners set North of this I. Rod.

Found I.P. August 1990, M 110-59

Doug. County Surveyors Office - Randall Smith, Stephen Flauser
June 8, 1993 - C.S. File 64/43-28

Found - 1 1/4" dia. iron rebar 2" below ground. (Set in M33-48)
Rebar measures 32" long. Corner lies in a field, owner requests removal of rebar as he will plow field deep in near future.

Accessories Found - (bearings based on M33-48)

3/4" I.R. bears N.0°08'01"W., 226.90 ft. Witness corner per M33-48.

3/4" I.R. bears N.0°08'01"W., 286.35 ft. Witness corner per M33-48.

5/8" I.R. bears N.41°07'07"E., 294.31 ft. (rec. N.41°40'08"E., 294.31 ft.) (M110-59)

Set - Witness Cor. 3/4" I.R. bearing N.0°08'01"W., 226.9 ft. from section corner is referenced and removed, I.R. measured 28" long.

A 2 3/8" dia. brass cap on a 1 1/4" O.D. dia. x 32" long iron pipe is set at referenced position, BC/IP protrudes 1" above ground.

Brass Cap marked:

DOUGLAS COUNTY SURVEYORS

T.27 S

WC

R	S 25	S 30	R
7	S 36	S 31	6
W			W

South 226.9 ft.

1993

OFFICE

Continued on next page.

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T.27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>3/4" I.R. is set along north edge of BC/IP, flush with ground.</p> <p>New Accessories - (from BC/IP Witness Cor.)</p> <p>5/8" I.R. bears S.88°28'25"E., 194.15 ft.</p> <p>5/8" I.R. bears S.89°55'16"W., 205.85 ft.</p> <p>5/8" I.R. bears S.89°58'14"W., 224.66 ft.</p> <p>5/8" I.R. bears N.72°41'46"W., 234.39 ft.</p> <p>5/8" I.R. bears N.0°24'40"W., 67.32 ft.</p> <p>3/4" I.R. bears N.0°08'01"W., 59.45 ft.</p>
<p>W.C. found OK by D. Edwards, Jan. 1998 - 1998-0010</p>
<p>DCSO-GIS Corner visitation - 7/19/2004 - Typed: 1/28/2011 - C.S. File 67/33-1</p> <p>-----</p> <p>Monument - BC/IP 1.25"</p> <p>Comment - OK</p>