

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & 25, T27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A Y.Oak 15" dia. bears S.23½°W., 225 lks. dist.
 A Y.Oak 22" dia. bears N.22°E., 242 lks. dist.

Roger Gee, For: E.G. Ziegler - Oct. 1967 - M 33-48

Set - 1¼" Iron Rod.
 Power Pole, N.74°58'W., 198.0 ft.
 12" Fir, S.87°40'E., 169.3 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J. Flause; June 15, 1993 - C.S. File 64/46-4

Found - 1¼" dia. iron rebar flush with ground. (1967 Gee)
 Power Pole cut off approx. 15 ft. high bears
 N.74½°W., 198.7 ft. (rec. N.74°58'W., 198.0
 ft.) May not be 1967 bearing pole.
 12" now 21" dia. D.Fir with a fully healed single
 blaze, bears S.87°E., 168.5 ft. (rec.
 S.87°40'E., 169.3 ft. distance is possible
 slope measurement.)
New - 8" dia. W.Oak, double blazed and scribed "¼ S30 CS
 BT" bears S.62½°E., 181.2 ft.
 45" dia. Maple, in yard of house - unmarked - bears
 N.33°W., 148.9 ft.
 SE corner of house bears N.11¼°W., 142.5 ft.
 Power pole 2013, bears N.74 3/4°W., 201.1 ft.
Note - Corner lies in open field. A fence post is set
 along north edge of rebar.

DCSO-GIS Corner visitation - 7/19/2004 - Typed: 1/28/2011 -
C.S. File 67/33-1

Monument - 1"
Comment - (needs) rehab