

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12 of T27-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set ¼ sec. post, from which  
    A Y.Oak, 10" dia. bears S.38°E., 29 lks. dist.  
    A Y.Oak, 12" dia. bears S.65½°W., 30 lks. dist.

Frank Cain, July 8, 1910 - "Old" Corner book, Page 98 & FB 55  
Page 26  
-----  
Reset by running through to sec. cor.  
    A B.Oak 18" dia., N.33°15'W., 23½ lks.  
    A B.Oak 30" dia., S.40°15'E., 20½ lks.

James W. Byron, Deputy County Surveyor - Milo Godfrey;  
Clete Putnam - December, 1960 - C.S. File 49/79-68  
-----  
Found - Scribed Oak stake.  
    B.Oak, now 36", S.40¼°E., 13.5 ft. Chopped scar  
        & found good scribing.  
    A stump hole & a down Oak tree bears N.33¼°W., 15.5'  
        Tree evidently died shortly after being marked  
        & all marks have rotted off.  
Set - Brass cap at corner alongside scribed stake mkd:  
    County Surveyor's Office 1960 T27S ¼ R7W  
    S12|S 7 R6W.  
New BTs - 11" I. Cedar N.84°E., 32.1 ft. mkd. ¼ S 7 CS BT.  
    20" B.Oak N.24°W., 123.3 ft. mkd. ¼ S12 CS BT.  
Corner falls in fence corner, fences N. S. & E. from corner.

Found B.C. & BTs - June, 1984, R. Ware, M 90-57  
Found B.C. May 1995 by H.Pieske - 1995-0068 A&B

FD. ok by Douglas Co. Surveyors Office - Randall W. Smith,  
Deputy - Stephen J. Flause - 10/28/2002 - C.S. File 66/34-47B