

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 1 of T. 27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which

A W.Oak, 13" dia. bears S.52¾W., 35 lks. dist.

A W.Oak, 12" dia. bears S.51°E., 84 lks. dist.

G.G. Stewart, Deputy - Julius Sindl; J.F. Johnson; T.E.
Littrel - May 17, 1922 - C.S. Vol. 3 Page 120

Found - Original bearing tree and set 1¼" iron pipe for
corner. Marked the following trees:

White Oak 10" dia. bears S.67½°E., 43.1 ft.

White Oak 30" dia. bears S.56°W., 22.5 ft. (orig.)

Douglas Co. Surveyors Off. R.B. Kimberling; P.L. Earle
March 23, 1978 - C.S. 59/46-4

Found - A 1¼" I.P. bent over 3" above ground bears S.58°E.,
1.2 ft. with a 1"x26" hollow drill rod at the
south edge set 6" below ground.

A 13" now 42" W.Oak bears S.52¾W., 23.1 ft. with a
well healed blaze. (OBT)

A 10" now 26" W.Oak bears S.65°E., 44.7 ft. (Rec.
S.67½°E., 43.1 ft.) with a well healed double
blaze. (Lower part of upper blaze is rotted)

Set - A 1" x 36" I.P. with a brass cap set 4" above ground
mkd: "Douglas County Surveyor T 27 S

R S 1|S 6 R

7 ¼ 6

W W

No new accessories. Corner is 40 ft. south of Orchard Lane, 1
ft. north of an East-West fence, 16 ft. west of a fence to
the south.

Douglas County Surveyors Office - Randall Smith; Stephen
Flause - Jan. 4, 1990 - C.S. File 64/5-2

Found - 1978 County 2½" dia. brass cap on a 1¼" O.D. iron
pipe that protrudes 3" above ground.

C O N T. N E X T P A G E

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for S. 6 & S. 1 of T27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 1¼" O.D. I.P. that protrudes 3" above ground bears S.58°E., 1.2 ft. from DCSO BC/IP.
1" hollow drill rod noted in 1978 as being 6" below ground along south edge of 1¼" O.D. I.P. not looked for.
13" now 44" dia. W.Oak with a fully healed blaze bears S.52¾°W., 23.1 ft. Orig. BT.
Orig. 12" W.Oak bearing S.51°E., 55.4 ft. is gone.
10" now 27" dia. W.Oak with a partially healed blaze no scribing visible bears S.66¾°E., 44.7 ft. (Rec. S.65°E., 44.7 ft.)
New BTs - 8" Ash double blazed and scribed "¼ S6 CS BT" bears S.36½°E., 13.0 ft.
8" Ash double blazed and scribed ¼ S6 CS BT" bears S.6°W., 13.8 ft.
Corner lies at the intersection of an east-west and south running fence line.

Found OK, Mark Heimburger, November 1991 - M 114-5
Found OK, May 1993 - D.Bentz, Partition Plat 1993-0058
Fd. Ok by D.Edwards, 3/97, M 126-50.

DCSO-GIS Corner visitation - 7/20/2004 - Typed: 1/28/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - OK

Fd. Ok by R. Quimby 8/2006 - 2006-0088

2