TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A W.Oak 13" dia. bears N.5°E., 35 lks. dist.
A Y.Oak 15" dia. bears S.6°W., 85 lks. dist.

James W. Byron, Deputy County Surveyor, Milo Godfrey;
Clete Putnam - January, 1961 - C.S. File 49/79-8

Found - Orig. 13" W.O., N.5°E., 23.1 ft. We open 7 find good reverse scribing "BT".
S.W. BT not found.
Set - Brass cap at corner mkd. County Surveyor's Office 1961 ¼ S 18 S 19 T27S R6W
Four way fence intersection.
New BTs - 7" W.O. bears S.61°E., 24.6 ft. scribed ¼ S19 CSBT.
5" W.O. bears N.12°E., 47.6 ft. scribed ¼ S18 CSBT.

Fd OK, D. Bentz, November 1991, M 114-19

DCSO-GIS Corner visitation - 8/2/2004 - Typed: 1/28/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - (needs) rehab

Fd. Ok by N. Hibbs Jan. 2005 - 2005-0010
Fd. BC & 3 BTs, C Sweeden, M162-68