TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A Y.Oak 9" dia. bears N.43¾°W., 42 lks. dist.
A Y.Oak 12" dia. bears S.88°E., 17 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey;
Clete Putnam - January, 1961 - C.S. File 49/79-8

Found - Orig. 9" now 14" B.Oak N.43¾°W., 27.7 ft. We open & find good scribing "T".
Orig. S.E. BT down & out of position.
Set - Brass cap at corner mkd. County Surveyor's Office, 1961 ¼ S7 T27S S18 R6W
Note: N. S. & E. fences.
New BTs - 16" B.Oak bears S.10°W., 15.5 ft. scribed ¼ S18 CSBT
18" R.Fir bears N.39°W., 26.0 ft. scribed ¼ S7 CSBT.

Found B.C., June, 1984, R. Ware, M 90-57

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 10/30/2002 - C.S. File 66/34-46

Found - 1961 DCSO brass cap iron pipe bent & leaning Westerly. Protrudes 15" out of ground. We straighten I.P. & set at plumb position now protrudes 4" out of ground (1961)
Corner lies along the south edge of a fence corner fence lines running N-S+W.
9" now 21 dia., B.Oak with a healed blaze bears N.43¾°W., 27.7 ft. (OBT)
16" now 27" dia., B.Oak with a fully healed double blaze bears S.10°W., 16.0 ft. (rec. S.10°W., 15.5 ft.)
18" now 36" dia., 2 ft. high D.Fir stump, with a fully healed lower blaze, bears N.39°W., 26.0 ft. (1961)
New - 27" dia., Madrone double blazed & scribed "¼ S18 CS BT" bears S.89°E., 47.5 ft. (Note: Old fence wire grown into tree)
10" dia., Madrone double blazed & scribed "¼ S18 CS BT" bears S.66°W., 30.0 ft.
Compass decl. 17½°E.

Fd. BC by M. Farr - 8/2010 - 2010-0033
Fd. BC & 5 BTs, C Sweeden, M162-68