

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 29, 30, 31 and 32, from which
A Y.Oak 15" dia. bears N.81¼°E., 155 lks. dist.
A Y.Oak 12" dia. bears N.62°W., 95 lks. dist.
A W.Oak 12" dia. bears S.61½°W., 91 lks. dist.
A W.Oak 14" dia. bears S.32°E., 108 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey;
Clete Putnam - January, 1961 - C.S. File 49/79-4

Found - Rock 6"x6"x24", set in fence corner, 20" in ground.
12" W.Oak, now 15" S.61½°W., 60.1 ft. showing good
scars.
14" W.Oak now 20" S.32°E., 71.3 ft. This tree has
been opened previously & face rotted.
Rotted Oak stump N.62°W., 62.7 ft. Too far gone to
find marks.
Down & rotting Oak to the NE approx. on bearing &
distance called for but cannot tell just
where it stood. Opened & found scribing "T 2".
Set - Iron pipe with brass cap alongside rock at corner
mkd. County Surveyor's office S30|S29 T27S R6W
1961 S31|S32
Blaze & scribe new BTs: 7" W.Oak S.3°W., 46.2 ft. mkd. T27S
R6W S31 CS BT.
14" W.Oak S.26°E., 71.1 ft. mkd. T27S R6W S32 CS BT.
7" W.Oak N.7½°E., 44.6 ft. mkd. T27S R6W S29 CS BT.
12" double W.Oak N.6°W., 80 ft. mkd. T27S R6W CSBT.

Doug. County Surveyors Office - Randall Smith, Stephen Flause,
May 12, 1993 - C.S. File 64/43-6

CONDITION REPORT ONLY

Found - 2½" dia. brass cap on a 1½" O.D. iron pipe,
protruding 15" above ground. (1961 Byron ren.)
Crumbled stones along north edge of BC/IP (stone
noted in 1961 Byron ren.)
12" now 14" dia. dead W.Oak, we open in two places,
no scribing or blazes found, bears S.56½°W.,
60.1 ft. (rec. S.61½°W., 60.1 ft.)

(Cont. Next Page)

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" now 21" dia. W.Oak with a previously opened rotted blaze, no scribing visible, bears S.33°E., 71.3 ft. (rec. S.32°E., 71.3 ft.) Orig. BT.

NW Orig. BT gone.

Possible rotted remains of Orig. NE BT Fd. near rec. brg and distance. No scribing or blazes found.

14" now 15" dia. W.Oak with a fully healed single blaze, bears S.31°E., 71.1 ft. (rec. S26°E., 71.1 ft.)

7" now 6" dia. W.Oak with a fully healed double blaze, bears N.5½°E., 45.2 ft. (rec. N.7½°E., 44.6 ft.)

12" now 10" dia. double trunked W.Oak with a fully healed double blaze on south trunk, center of root crown bears N.7½°W., 80.0ft. (rec. N.6°W., 80.0 ft.)

Note - Corner lies near the intersection of a north and west running fence lines. Intersection of fences is 2½ ft. northwest of BC/IP.

Fd. O.K. - Donald Bentz, March 1993 - Vol. 18 Pg. 4 A,B,&C