

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post to Secs. 7, 8, 17 and 18, from which
A Y.Oak, 15" dia. bears S.28°W., 38 lks. dist.
A Y.Oak, 12" dia. bears N.67°W., 21 lks. dist.
A Laurel, 18" dia. bears N.52°E., 53 lks. dist.
A W.Oak, 10" dia. bears S.62½°E., 126 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey;
Clete Putnam - December 1960 - C.S. File 49/79-80

Found - Orig. 18" now down 28" Laurel N.52°E., 35.0 ft. We
open & find good reverse scribing "T".

No other orig. BTs found.

Set - Brass cap at corner mkd. County Surveyor's S 7 | S8
Office 1960 S 18 | S17
T27S R6W

(See CS File for sketch of fences.)

New BTs - 20" B.O. N.67°W., 13.9 ft. scribed S7 T27S R6W CS
BT.

18" R.Fir S.58°W., 134.0 ft. scribed S18 T27S
R6W CS BT.

7" W.Oak S 87½°E., 119.3 ft. scribed S17 CS BT.

20" B.Oak N.66°E., 81.9 ft. scribed S 8 T27S
R6W CS BT.

Found B.C. June, 1984, R. Ware - M 90-57

DCS0-GIS Corner visitation - 8/4/2004 - Typed: 1/28/2011 -
C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK