

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor for Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A Y.Oak 16" dia. bears S.55°W., 83 lks. A Maple, 12" dia. bears N.75°E., 33 lks.</p>
<p>James W. Byron, Deputy County Surveyor - Milo Godfrey; Clete Putnam - December, 1960 - C.S. File 49/79-80 ----- Found - Orig. 12" now 18" Maple snag, shows good reverse scribing "¼S", N.75°E., 21.8 ft. Orig. 16" now 22" B.Oak S.55°W., 54.8 ft. shows good scars. Set - Brass cap at corner mkd. County Surveyors Office 1960 ¼ S7 S8 T27S R6W New BTs - 20" R.Fir bears N.14½°E., 19.8 ft. scribed ¼ S8 C.S. B.T. 5" B.Oak bears S.62°W., 24.3 ft. scribed ¼ S7 CS BT</p>
<p>Found June, 1984, R. Ware, M 90-57</p>
<p>Douglas County Surveyors Office - Randall Smith & Stephen Flause - 4/22/96 - C.S. 64/66-13 ----- Found - 2½" dia. brass cap on a 1½" O.D. by 36" long iron pipe was found out of ground by property owner. 16" now 25" dia. B.Oak, with a fully healed blaze, bears S.55°W., 52.9'. 12" now down and rotted 12" maple, no scribing found, roots bear N.75°E., 21.8'. 20" now 26" dia. D.Fir, with a fully healed double blaze, bears N.14½°E., 19.1'. 5" now 8" dia. B.Oak, with a fully healed single blaze, bears S.62°W., 24.3'. Set- 1960 DCS0 BC/IP is set at a position determined from BT's as noted on front of page. BC/IP protrudes 7" above ground. (Note we added stamping to BC "RESET 1996". New BTs- 12" dia. Madrone, bark scribed "¼ S7 CS BT", bears N.74°W., 25.3'. corner lies on a steep north slope approx. 20' west of a down north - south fence.</p>
<p>continued next page</p>

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor for Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCS0-GIS Corner visitation - 8/3/2004 - Typed: 1/28/2011 -
C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK

Ken Hoffine - For: TBT Properties LLC - 7/2016 - C.S. 65/92-
12

Found - 1960 DCS0 brass cap as per C.S. 64/66-13
30" D.Fir bears N.16°E., 19.8' (rec. N.14½°E.,
19.1') tag and healed face.
25" B.Oak bears S.54°W., 52.6' (rec. S.55°W., 52.9')
tag & healed face.
15" Madrone bears N.73½°W., 25.2' (rec. N.74°W.,
25.3') tag and visible bark scribing.
Corner lies on steep north slope 0.5' above ground level.
T-post 5.0' north.