

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A Y.Oak 15" dia. bears S.66½°W., 73 lks. dist.
A W.Oak 6" dia. bears N.64½°W., 98 lks. dist.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam
January, 1961 - C.S. File 49/79-20

Found - 15" B.O., now 24", S.66½°W., 48.2 ft. chopped
open & find good scribing "S".
14" W.O., N.64½°W., 64.7 ft. Did not show scars.
Did not open.
Set - Iron pipe with brass cap mkd. County Surveyors
Office, 1961 ¼ S29 S32 T27S R6W.
New BTs - 14" Madrone S.73°W., 48.7 ft. mkd. ¼ S32 CS BT.
11" B.Oak N.56½°W., 48.0 ft. mkd. ¼ S29 CS BT.
A fence line running north & south bears west, 40 ft.

Doug. County Surveyors Office - Randall Smith, Stephen Flauser
May 12, 1993 - C.S. File 64/43-25

Found - 2½" Brass cap on a 1½" O.D. iron pipe, protruding
12" above ground.
15" now 26" dia. B.Oak with a fully healed blaze,
bears S.65°W., 48.2 ft. (rec. S.66½°W., 48.2
ft.) Orig. BT.
14" now 14" W.Oak recorded in 1961 renewal as
bearing N.64½°W., 64.7 ft. We open in two
places. No blazing or scribing found. The above
bearing and distance is same as orig. 6" NW BT.
We find bearing and distance to be N.65½°W.,
64.0 ft. Orig. BT ?
14" now 18" dia. Madrone with a fully healed double
blaze, bears S.71°W., 48.7 ft. (rec. S.73°W.,
48.7 ft.)
11" now 16" dia. B.Oak with a fully healed double
blaze, bears N.57½°W., 48.0 ft. (rec. N.56½°W.,
48.0 ft.)

New Accessories -

14" dia. W.Oak that we opened in two places looking
for scribing blazed above and below axed
openings and scribed "¼ S29 CS BT" bears
N.65½°W., 64.0 ft.

Continued on next page

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor for Secs 29 and 32

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

17" dia. D.Fir double blazed and scribed "¼ S32 CS
BT" bears S.12½°E., 7.2 ft.
Note - North-south fence line is 40 ft. west of corner.