

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 17 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ sec. post, from which  
    A W.Oak 24" dia. bears S.31¼°E., 586 lks. dist.  
    A Y.Oak 24" dia. bears N.58°34'E., 1169 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey;  
Clete Putnam - December 1960 - C.S. File 49/79-2

-----  
Found - Orig. 24" now 36" W.Oak, S.31¼°E., 386.8 ft. We  
          open and find good scribing "S".  
          Orig. N.E. BT not found.  
Set - Brass cap at corner mkd. County Surveyor's Office  
      1961 ¼  $\frac{S}{S}$   $\frac{17}{20}$  T27S R6W  
New BTs - 15" W.Oak bears N.34°E., 31.0 ft. scribed ¼ S17 CSBT  
          7" B.Oak bears S.47°W., 10.0 ft. scribed ¼ S20 CSBT.

Found OK August 1984, Don Bentz, M 97-23  
Fd. DCSO BC & Accessories, 5/91, M. Heimbürger, M 113-31  
Fd. OK by DeGroot, Aug. 1994 - M119-71.

DCSO-GIS Corner visitation - 8/2/2004 - Typed: 1/28/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP - 1.25"  
Comment - (needs) rehab