

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set ¼ sec. post, from which A Y.Oak 18" dia. bears N.49°E., 53 lks. dist. A Y.Oak 9" dia. bears S.66°W., 36 lks. dist.	
James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - January, 1961 - C.S. File 49/79-15 ----- Found - Both orig. BTs: Orig. 18" now 40" B.Oak N.49°E., 35.0 ft. Shows scar. I do not open. Orig. 9" now down Oak, partly rotted. We find good reverse scribing "S". Note: Corner 10 ft. west of wire fence. Set - Brass cap at corner mkd: County Surveyor's Office, 1961 ¼ S32 S33 T27S R6W New BTs - 12" W.Oak N.15°E., 20.5 ft. scribed ¼ S33 CS BT. 10" W.Oak N.58°W., 32.9 ft. scribed ¼ S33 CS BT.	
Doug. County Surveyors Office - Randall Smith - Stephen Flause - May 13, 1993 - C.S. File 64/43-26 ----- Found - 2½" Brass cap on a 1½" O.D. iron pipe, protruding 13" above ground. 18" Y.Oak now 40" dia. B.Oak with a fully healed previously opened blaze, bears N.52½°E., 35.0 ft. (rec. N.49°E., 35.0 ft.) Orig. BT. 9" now remains of rotted roots, bear S.66°W., 23.8 ft. Orig BT. 12" now 14" dia. W.Oak with a fully healed double blaze, bears N.15°E., 20.5 ft. 10" now 12" dia. W.Oak with a fully healed double blaze, bears N.58°W., 31.8 ft. (rec. N.58°W., 32.9 ft., distance hits trunk at a horizontal from BC/IP. New - 11" W.Oak double blazed and scribed "¼ S32 CS BT" bears N.5¾°W., 39.4 ft. Note - Corner lies 9 ft. west of a north-south fence line.	
DCSO-GIS Corner visitation - 8//2004 - Typed: 1/28/2011 - C.S. File 67/33-1 ----- Monument - BC/IP - 1.25" Comment - OK	