

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A W.Oak 20" dia. bears S.76°W., 37 lks. dist.
 A Y.Oak 15" dia. bears N.43½°E., 110 lks. dist.

James W. Byron, Deputy County Surveyor- Milo Godfrey; Clete Putnam - January 1961 - C.S. File 49/79-11

Found - B.Oak now 24", N.43½°E., 72.6 ft., dead but standing cut open & found good scribing "BT"
 Old stump bears S.83°W. (instead of S.76°W.) 24.4 ft. no evidence of scribing.
Set - Brass cap mkd. County Surveyor's Office, 1961
 ¼ S20|S21 T27S R6W.
New BTs- 10" B.Oak N.32°W., 18.3 ft. mkd. ¼ S20 CS BT.
 12" W.Oak N.16½°E., 28.1 ft. mkd. ¼ S21 CS BT.
Corner is in old wooden fence line & 2 ft. south of present wire fence running east and west. A fence corner - fences E. W. & N. lies west of corner a distance of 94 ft.

Found OK, Dec. 1980, J. Gosson, M 86-17

Doug. County Surveyors Office - Randall Smith-Stephen Flause. May 10, 1993 - C.S. File 64/43-12

Found - 2½" dia. Brass cap on a 1½" O.D. iron pipe protruding 18" above ground.
 10" now 11" dia. B.Oak with a fully healed double blaze, bears N.32°W., 18.3 ft. (1961 Byron)
 12" now 15" dia. W.Oak with a fully healed double blaze, bears N.16½°E., 28.1 ft.
 15" now 22" dia. down and rotted oak, no scribing or blazes visible, root hole bears N.43½°E., 72.6 ft. (orig. BT)
 20" now 20" dia. 2 ft. high rotted oak stump, no scribing or blazes visible bears S.83°W., 26.8 ft. (rec. from 1961 ren. S.83°W., 24.4 ft.)
New Accessories -
 7" I.Cedar, double blazed and scribed "¼ S20 CS BT" bears S.63°W., 46.2 ft.
 6" Ash, double blazed and scribed "¼ S21 CS BT" bears S.65½°E., 39.3 ft.
Note - Cor. lies 2' SE of an E/W & south running fence line.

Fd. OK - Don Bentz - June 1996 - Vol. 19 Pg. 9 A-K
Fd. OK - by Heimburger - Jan. 1999 - M131-35

