

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 16, 20 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 16, 17, 20 and 21, from which  
A Laurel, 14" dia. bears N.88¼°E., 240 lks. dist.  
A Y.Oak, 9" dia. bears S.45½°E., 131 lks. dist.  
A W.Oak, 6" dia. bears N.41½°W., 84 lks. dist.  
A W.Oak, 20" dia. bears S.63°W., 256 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey;  
Clete Putnam - December 1960 - C.S. File 49/79-82

-----  
Found - Orig. 6" now 18" W.Oak N.41½°W., 55.4 ft. shows  
good scars. I do not open.  
Orig. 20" now 32" W.Oak S.63°W., 169.0 ft. We  
find bearing should be S.59°W. Shows scars.  
Old Laurel stump checks dist. for N.E. BT. Bearing  
record N.88½°E. We find should be N.83°E.  
Orig. 9" now 18" B.Oak S.45¼°E., 86.5 ft. We find  
to be 82.5 ft. We open & find good scribing.  
Also find 1½" iron pipe at corner & East West fence.  
Set - Brass cap at corner mkd: County Surveyor's Office  
1960 S17 | S16 T27S R6W  
S20 | S21  
New BTs - Orig. N.W. BT is OK.  
5" W.Oak bears S.66°E., 42.4 ft. scribed S21 CS BT.  
6" W.Oak bears N.39°E., 50.0 ft. scribed S16 T27S  
R6W CS BT.  
10" W.Oak bears S.69°W., 122.8 ft. scribed S20 T27S  
R6W CS BT.

Douglas County Surveyors Office - Randall Smith; Stephen  
Flause - March 1, 1990 - C.S. File 64/6-3

-----  
CORNER REPORT ONLY

Found - A 1960 DCS0 2½" dia. brass cap on a 1¼" O.D. I.P.  
which protrudes 18" above ground.  
A 1½" O.D. iron pipe protrudes 11" above ground  
bears S.62°E., 0.7 ft. from DCS0 BC/IP.  
14" now rotted madrone stump of indeterminate size  
with a cluster of new madrones growing from  
stump roots, bears N.80½°E., 158.4 ft. (Orig.  
rec. N.88¼°E, Byron, N.83°E) Poss. orig. BT.

cont. next page:

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

9" now 20" dia. B.Oak with a previously opened blaze, no scribing visible bears S.47½°E., 81.6 ft. (Orig. rec. S.45¼°E., 86.5 ft. Byron's S.45¼°E., 82.5 ft.) Orig. BT.

6" now 21" dia. W.Oak with a fully healed single blaze, bears N.41½°W., 55.4 ft. (agrees w/rec) Original BT.

20" now 28" dia. W.Oak with a previously opened blaze, no scribing visible, bears S.60½°W., 169.0 ft. (Rec. S.63°W) Orig. BT.

5" now 6" dia. W.Oak with a fully healed double blaze bears S.66°E., 42.4 ft. (agrees w/rec)

6" now 7" dia. W.Oak with a fully healed double blaze bears N.39°E., 50.0 ft. (agrees w/rec)

10" now 10" dia. W.Oak with a fully healed double blaze bears S.69°W., 121.9 ft. (Rec. S.69°W., 122.8 ft.)

Corner lies at intersection of east and south running ridge on north side near top.

FD ok by D. Bentz, Feb. 1995 - 1995-0101  
Fd. OK by M. Farr, April 2003 - 2003-0034