TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A Y.Oak, 13" dia. bears S.63°W., 54 lks. dist.
A Y.Oak, 8" dia. bears N.3¾°E., 51 lks. dist.

Roger Gee, For: Ray Graves, Nov. 1966 - M 32-42

Set - 1" x 48" iron rod at mid point on section line.
BT - 48" B.Oak bears N.31°30'W., 132.07 ft.

Donald Bentz, LS #839 - For: Steve Lawnicki, May, 1988 - M 106-23

Found - 48" B.Oak N.31°30'W., 132.07 ft.
Set - 5/8" iron rod with cap mkd. "Bentz Surv. Inc.".

Bruce Shaner, surveyed for: Joyce Conn, Sept. 1996 - M 125-62 A & B; Narr. C.S. 65/10-2 A & B; Corner report C.S. 65/8-7.

Found - 5/8" iron rod set by Bentz in 1988, from which:
48" Black Oak BT with overgrown face, now blown down, bears N.31½°W., 132.1 ft.
Set - 3" x 28" alum. pipe with a 3½" alum. cap, marked:
T 27 S R 6 W W.M.
¼
17 | 16
RLS 430 1996
New - 14" Madrone BT, bears S.53°W. 85.4 ft. scribed "¼ S17 BT"
12" Madrone BT, bears N.31°W. 48.3 ft. scribed "¼ S17 BT"
6" Oak BT, bears N.10°E. 50.8 ft. scribed "¼ S16 BT"
6 ft. steel fence post, set North, 1.0 ft.
6 ft. steel fence post, set West, 1.0 ft.
Note - Corner is 85 ft. East of N-S fenceline.

Fd 3½" alum. Cap - by B. Knapp - 10/2020 - 2020-0045