

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set 1/4 sec. post, from which  
A Y.Oak 18" dia. bears N.67 1/2°E., 177 lks. dist.  
A Y.Oak 13" dia. bears S.65 1/2°E., 198 lks. dist.

Wilford N. Haines, For: J. H. Connon - August, 1964  
M 28 - 50 and M 28 - 51  
-----

Found - No trace of original 1/4 corner nor orig. BTs.  
Set - 1/2" x 48" Bolt  
Scribed - 10" W. Oak S.36°E., 52.8 ft.  
12" W. Oak N.27°E., 70.7 ft.

Found 3/4" I.Rod - Fd. BTs OK, Dec. 1980, J. Gosson  
Found OK, Don Bentz, July, 1984, M 97-31

Doug. County Surveyors Office - Randall Smith-Stephen Flause.  
May 25, 1993 - C.S. File 64/43-10  
-----

Found - 3/4" Iron bolt, protrudes 7" above ground, recorded  
as a 1/2" bolt in Haines 1964 renewal.  
10" now triple trunked W.Oak with a fully healed  
double blaze on 14" dia. westerly trunk. Root  
crown bears S.37 1/2°E., 52.8 ft. (rec. S.36°E.,  
52.8 ft., brg. and slope dist. hit scribed  
trunk approx. 4 ft. above ground).  
12" now 14" dia. W.Oak with a fully healed double  
blaze, bears N.27°E., 70.7 ft.  
Set - Position of iron bolt is referenced and a 2 3/8"  
Brass cap on a 1 1/4" O.D. by 32" long iron pipe  
is set at referenced position. BC/IP protrudes  
9" above ground. Iron bolt is along westerly  
edge of BC/IP protruding 7" above ground.

Brass Cap marked:

DOUGLAS COUNTY SURVEYORS

T 27 S

1/4 S 21 R 6 W

S 28

1993

OFFICE

(Cont. Next Page)

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 & 28.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -  
16" dia. Ash double blazed and scribed "¼ S21 CS BT"  
bears N.03½°W., 36.2 ft.  
4" dia. W.Oak double blazed and scribed "X BT" bears  
S.33°W., 11.3 ft.  
Note - Bolt is south 1 ft. from an easterly-westerly running  
fence line.