

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Secs. 16 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set ¼ sec. post, from which  
    A Y.Oak, 7" dia. bears N.43°W., 32 lks. dist.  
    A W.Oak, 13" dia. bears S.14¼°W., 390 lks. dist.

---

Wilford N. Haines For: J.H. Connon - August, 1964  
M 28-50 and M 28-51  
-----  
Found - No trace of orig. BTs, but this point is close to  
          calculated corner and has ben used for many  
          years so I take it the most logical position  
          for ¼ corner.  
Set - 1" x 1" x 36" T. Iron by pipe and scribed:  
      12" W.Oak, N.03½°E., 17.8 ft.  
      16" W.Oak, S.22°E., 18.5 ft.

---

Doug. County Surveyors Office - Randall Smith-Stephen Flauser  
May 19, 1993 - C.S. File 64/43-24  
-----  
Found - 5/8" Iron rod found S.0°04'52"W., 1.82 ft from  
          calculated corner position (agrees with  
          M109-32)  
      Note - This I.R. was not set as ¼ corner.  
          Haines T-Iron not found.  
Accessories Found - (Brgs. & Dist's. from calculated corner  
          position.  
          13" now 19" dia. W.Oak with a fully healed double  
          blaze, bears S.24°15' 45"E., 18.5 ft. (agrees  
          with M109-32) Compass bearing S.22°E., 18.5 ft.  
          N.E. W.Oak from 1964 Haines renewal is gone.  
New Accessories -  
      Fd. 3/4" I.R. bears N.25°05'43"E., 88.15 ft.  
      Fd. 3/4" I.R. bears N.68°17'45"E., 63.49 ft.  
      Fd. 5/8" I.R. bears S.0°04'52"W., 1.82 ft.  
      Fd. 5/8" I.R. bears N.89°52'36"W., 118.82 ft.  
      Fd. 5/8" I.R. bears S.60°12'25"W., 70.56 ft.  
Note - Bearings based on M109-32.  
      Calculated corner position is approx. 2 ft. off of  
          south edge of pavement and 6 ft. north of a  
          fence corner in gravel shoulder of Co Rd. #  
          341.

---

Fd. 5/8" I.R. set on M 109-32, by D. Bentz - M 120-60 Aug.  
1994 (W.C. to the 1/4 corner)

---

Fd. 5/8" IR WC 1/2019 M Calvert M175-45