

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A W.Oak, 12" dia. bears S.82½°W., 198 lks.
 A W.Oak, 12" dia. bears N.12°E., 147 lks.

James W. Bryon; R. Irving; J. Fee - For: Earl Wiley
April, June, 1955 - C.S. File 46/155, M 7 - 23

1/4 Corner located on true line & at midpoint N.W. Corner
Section 22 & S.W. Corner Section 22.
Set - Brass cap 1" above surface mkd. ¼ S 21|22 County
Surveyor's Office, 1955.
Set - ¾" I.R. at base of 12" anchor post (fence) scribe
B.O.
Blaze & scribe 12" W.O. ~~N.6°03'30"W.~~ N.62°W., (1/11/61 L.L.)
134.5 ft. scribed ¼ S21 CS BT.

Found OK, Dec. 1973, Don Garrett, M 52 - 14
Found OK, Dec. 1980, Jim Gosson, M 86 - 17

Doug. County Surveyors Office - Randall Smith, Stephen Flauser
May 10, 1993 - C.S. File 64/43-5

Found - 2½" Brass cap on a 1½" O.D. iron pipe protruding 1"
above ground. (1955 Byron)
12" now 24" dia. W.Oak with a fully healed single
blaze, bears N.62°W., 134.5 ft.
¾" I.R. at fence corner, no scribing found on
fence corner post, I.R. bears S.75°E., 195.6
ft. (agrees with tag on fence post - no brg.
and dist. to I.R. found in 1955 Byron renewal.
New Accessories -
 24" dia. W.Oak double blazed and scribed "¼ S21
 CSBT" bears N.83 ¾°W., 123.2 ft.
 16" dia. Ash double blazed and scribed "¼ S22 CSBT"
 bears N.24½°E., 102.8 ft.

Found OK Nov. 1995 by Bentz - 1996-0020

Found OK by K. DeGroot, Aug. 1999 - M133-28
Fd Ok by A DeGroot, June 2018 - 2018-0021A&B