

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 2, 3, 10 and 11, from which  
A Y.Oak 20" dia. bears S.71½°E., 656 lks. dist.  
A W.Oak 18" dia. bears N.74°E., 534 lks. dist.  
A W.Oak 12" dia. bears S.89¾°W., 235 lks. dist.  
A W.Oak 10" dia. bears N.85¾°W., 475 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - Jan. 1961 - C.S. File 49/79-42

-----  
Found - Orig. 20", now 30" Oak stump S.71½°E., 433.0 ft., shows good reverse scribe marks on chip.  
Orig. 18", now 32" Oak stump N.74°E., 352.4 ft. We open & find good scribe "BT"  
BTs to West in field not found.  
Set brass cap at corner mkd: County Surveyors  $\frac{S\ 3}{S\ 2}$  T27-6  
Office 1961  $\frac{S10}{S11}$   
Set - ¾" iron rod 30.7 ft. East of sec. cor. & in field fence line.  
30" W.Oak bears N.68¾°E., 275.4 ft. scribed S2 T27S R6W CS BT.  
15" B.Oak bears S.30°W., 517.0 ft. scribed S10 T27S R6W CS BT.  
No trees near to N. W. S. E.

Fd. Ok by G. Baughman, 12/1983 - M 95-71

Douglas Co. Surveyors Off. - Randall Smith; Stephen Flause October 18, 1988 - C.S. File 62/59-7

-----  
Found - A 1961 County B.C. on a 1¼" I.P. protrudes 16" above ground & leans 4" southwest.  
(Bearings & distances taken to plumb of brass cap/iron pipe)  
18" now 36" dia. 2½ ft. high rotted oak stump with a previously opened blaze, no scribing visible bears N.71½°E., 352.4 ft. (Rec. N.74°E) (Orig.)  
20" dia. Oak now a depression with roots is found, bears S.74°E., 433.0 ft. (Rec. S.71½°E) (Orig.)  
30" now 36" dia. W.Oak with a fully healed double blaze bears N.66½°E., 275.4 ft. (Rec. N.68¾°E.)  
15" now 26" B.Oak with a fully healed double blaze bears S.28½°W., 515.6 ft. (Rec. S.30°W. 517.0 ft. dist. is to center of trunk)  
¾" iron rod protruding 8" above ground is found in an old dilapidated fence line, bears East, 30.7'

continued next page

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec Cor 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - Brass cap iron pipe returned to plumb position and a 2 ft. mound of stone set around base.  
Corner lies on northwesterly side of a northeasterly ridge near its base.

Found OK and used, May, 1990, M 110-24  
Found brass cap, Dec. 1991, D. Bentz, MLP 1992-0004  
Fd brass cap, Jun. 1994, R. Ware, 1995-0006

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 5/5/2004 (Recorded 11/16/2006) - C.S. File 67/14-37

-----  
Found - A 2½" dia. brass cap (properly mkd) on a 1¼" O.D. iron pipe protrudes approx. 1 ft. above a loose mound of stone.  
No evidence of orig. BTs fd.  
Three noted references from 1961 renewal:  
A ¾" dia. iron rod protruding approx. 8" above ground in remnants of old N-S fence line bears N.88¾°E., 30.4 ft. dist. (rec. East, 30.7 ft.)  
A 30" W.Oak now a dead 36" D.B.H. W.Oak with a fully healed double blaze bears N.66½°E., 275.4 ft. dist. (agrees w/1988 rec.)  
A 15" B.Oak, now a 29" D.B.H. B.Oak with a fully healed double blaze bears S.28½°W., 517.0 ft. dist. (agrees well w/1988 rec S.28½°W., 515.6 ft)  
New - 23" DBH, double blazed & scribed "T27S R6W S2 CS BT" most westerly trunk of a double trunk W.Oak, the root crown of which bears N.18¾°E., 403.9 ft.  
25" DBH, W.Oak scribed "T27S R6W S2 CS BT" on a double blaze, bears N.49¾°E., 314.2 ft.  
The most northeasterly corner of lot 3 of Darley Subdivision which is a 5/8" iron row with a plastic cap protruding 0.2 ft. above ground bears S.11½°W., 311.4 ft. (rec. S.13¾°W., 311.4 ft.)  
The most northerly corner of a square concrete, surface well casing (3½'x3½' walls are approx. ½ ft. thick) bears S.59½°W., 362.1 ft.  
Note - Monument is in open field near base of ridge.  
Compass decl. 16½°E.