

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T26-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post (on summit of hill N.20°E and S.20°W) cor. to
secs. 2, 3, 34 and 35, from which

- A W.Oak 6" dia. bears S.57¾°W., 67 lks. dist.
- A Y.Oak 6" dia. bears N.86°W., 43 lks. dist.
- A Y.Oak 10" dia. bears N.10°E., 120 lks. dist.
- A Y.Oak 8" dia. bears S.73°E., 136 lks. dist.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete
Putnam - January, 1961 - C.S. File 49/79-41

Found - Orig. 6" now 18" W.Oak S.57½°W., 44.2 ft. center
rotted.
Orig. 6" now 24" B.O. N.86°W., 28.4 ft. shows scar.
Orig. 10" now 34" B.O. N.10°E. 79.2 ft. We open &
find good scribing "W".
Orig. 8" now 24" B.O. S.73°E., 89.8 ft. shows scar.
Set -Brass cap at cor. mkd. County Surveyor S34|S35 T26S R6W
Office, 1961 S 3|S 2 T27S
New BTs - 24" B.O. N.86°W., 28.4 ft. (O.B.T.) scribed S34
T26S R6W CS BT.
12" W.O. N.20°E., 84.0 ft. scribed S35 T26S R6W
C.S B.T.
9" B.O. S.15°E., 53.0 ft. scribed S2 T27S R6W CSBT.
9" W.O. S.29°W., 14.7 ft. scribed S3 T27S R6W CSBT.

Found OK, Bruce Rogers, November, 1982 - M 93-27