

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ sec. post, from which  
    A W.Oak, 18" dia. bears N.43¾°E., 996 lks. dist.  
    A W.Oak, 22" dia. bears N.14¼°W., 1242 lks. dist.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam  
January, 1961 - C.S. File 49/79-21

-----  
Found - Remains of 2 old Oaks that check record distance  
          & bearing. Each shows pieces of old windows  
          & axe work. No scribing found.  
          No evidence of any old Oaks that would be closer  
          to corner. The location of cor. checks by  
          compass & pacing from known corner.  
Set - Brass cap at corner mkd. County Surveyor's Office  
      1961, South ¼ S35 T27S R6W  
New BTs - 6" Ash bears S.49°W., 122.0 ft. scribed S¼ S35 CSBT  
          8" W.Oak, N.12°W., 479.8 ft. scribed ¼ S35 CS BT.  
          6" W.Oak, N.3½°E., 330.6 ft. scribed ¼ S35 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J.  
Flause; June 22, 1993 - C.S. File 64/46-6

-----  
Found -  
    2½" Brass Cap on a 1¼" O.D. iron pipe, leans 1 ft. south  
    of plumb protruding 14" above ground. (1961 DCS0 BC)  
    18" now down and rotted Oak, old axe mark found, root  
    hole bears, N.44 ¾°E., 653.7 ft. (rec. N.43 ¾°E.  
    657.4 ft.)  
    22" now down with scattered Oak remains found near record  
    bearing & distance (N14¼°W., 819.7 ft.) Orig. BT  
    8" now 11" dia. W.Oak, with a fully healed double blaze,  
    bears N.12 ¾°W., 480.8 ft. (rec. N.12°W., 479.8  
    ft.) 1961 BT  
    6" now 11" dia. W.Oak, with a fully healed invisible  
    blaze, I opened and find illegible scribe marks,  
    bears N.2 ¾°E., 332.2 ft. (rec. N 3½°E., 330.6')  
    SW Ash from 1961 renewal now gone.  
Note - BC/IP returned to plumb position, protrudes 14" above  
      ground by a loose mound of stones.  
New Accessories -  
    18" B.Oak, double blazed and scribed "¼ S35 CS BT" bears  
    N.63½°E., 433.4 ft. (Cont. Next Page)

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories continued -  
23" W.Oak, double blazed and scribed "¼ S35 CS BT" bears  
N.40½°W., 559.7 ft.  
Note - Corner lies 3 ft. north of most northerly sewer ponds  
north fence line.

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16