

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 23, 24, 25 and 26, from which
A Y.Oak, 36" dia. bears N.83 $\frac{3}{4}$ °E., 786 lks. dist.
A W.Oak, 15" dia. bears S.56 $\frac{3}{4}$ °E. 421 lks. dist.
A W.Oak, 28" dia. bears S.44 $\frac{1}{2}$ °W., 603. lks. dist.
A Y.Oak, 20" dia. bears N.1 $\frac{1}{2}$ °W., 968 lks. dist.

M. B. Germond Co. Sur. - Wit. A.D. Hawn; F.C. Frear
Oscar Lindsey - Jan/Feb, 1917 - F.B. 44 Pg. 31-34
F.B. 69 Pg. 65

Set in corner from two old original bearing tree stumps,
letters legible. New corner is 2" x 36" iron pipe (gal)
from which:

A W.Oak 15" dia. bears N.00°10'E., 8.72 chs. Nail
in the tree marks exact sec. line N.
A W.Oak 16" dia. bears S.75°00'W., 4.355 chs.
A W.Oak 8" dia. bears S.16°07'E., 3.88 chs.

Found OK, V.R.T. - 3/1/71 - C.S. 53/38-22

Doug. Co. Surveyor Office - Karen Reed; P. Earle; F. Silagy;
December 13, 1978 - C.S. 60/17-31

Found - A 2" x 36" galv. I.P. approx. 1" above ground. In
center of pipe is a wooden hub with a PK nail.
Pipe located in middle of horse pasture.
A 16" W.Oak, now 30" bears S.77°W., (Rec. S.75°W.)
287.4 ft. with healed over double blaze. Also
on tree L and A bark scribed.
A 8" W.Oak now 29" bears S.14°E., (Rec. S.16°E.)
256.6 ft. (Rec. 256.1 ft.) with healed over top
and bottom blaze, middle part was chopped out
at one time, visible "7S".
A 15" W.Oak, now a 20" bears N.2°W., (Rec. N.0°E.)
575.5 ft. with rotted out blaze.
No original evidence left.

No new monument set.

New BTs - A 7" W.Oak bears N.27°E., 365.2 ft. with double
blaze mkd. "T27S R6W S24 CS BT".

A 19" Ash bears N.58°W., 230.0 ft. with double blaze
mkd. "T27S R6W S23 CS BT".

Found OK, Dec. 1994 by D.Collier - 1995-0063
Fd. Ok by K.DeGroot 7/97 - 1997-0086