

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ sec. post, from which  
    A Y.Oak 12" dia. bears N.11°W., 46 lks. dist.  
    A Y.Oak 14" dia. bears N.46°E., 63 lks. dist.

Milo E. Godfrey, Deputy - Wm. Stoffel; M. Stone; M. Darby  
May, 1964 - C.S. File 49/79-89

-----  
Found - 14" B.Oak N.11°W., 30.4 ft. opened & found good  
          reverse scribing. Did not found NE tree.  
Set - Brass cap at cor. mkd. County Surveyors Office 1964  
          T 27S R6 W ¼ S 36  
New BTs - 13" B.Oak N.50°E., 34.9 ft. mkd. ¼ S36 CS BT.  
          17" B.Oak N.77°E., 25.5 ft. mkd. ¼ S36 CS BT.  
Corner lies on very steep N.W. slope above S. Umpqua River.  
(This corner is on N. line T28S R6W)

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J.  
Flause; July 20, 1993 - C.S. File 64/46-3

-----  
Found - 2½" dia Brass Cap on a 1¼" O.D. iron pipe  
          protruding 14" above ground. (1964 Godfrey)  
          12" now 12" dia. dead Oak with a previously opened  
          blaze, reverse scribing found, bears N.11°W.,  
          30.4 ft. (orig. BT)  
          13" now 16" dia. B.Oak with a fully healed single  
          blaze, bears N.50°E., 34.9 ft. (1964 Godfrey)  
          17" now 19" dia. B.Oak with a fully healed double  
          blaze, bears N.77°E., 25.5 ft. (1964 Godfrey)  
New Accessories -  
          7" dia. W.Oak, double blazed and scribed "¼ S36 CS  
          BT" bears N.10½°E., 39.8 ft.  
          11" dia. B.Oak, double blazed and scribed "¼ S36 CS  
          BT" bears N.63°W., 29.2 ft.

Fd. DCSO Brass Cap 7/2022 J. Estabrook - 2022-0035