

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; & S. 30, 31, T. 27-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 31, 36, 25 and 30, from which  
A W.Oak, 26" dia. bears S.29°W., 182 lks. dist.  
A W.Oak, 16" dia. bears S.13½°E., 287 lks. dist.  
A W.Oak, 22" dia. bears N.40½°E., 150 lks. dist.  
A G.Oak, 9" dia. bears N.32½°W., 188 lks. dist.

Claude Crocker; Arthur Boyer; J.H. Wolford; B.A. Lane  
1934-37-38 - Volume 4 Pages 50-58

-----  
This corner was gone but was set by proportional distances  
between ¼ to 25 and 30 and the ¼ to 31 and 36.  
Set - ¾" x 30" iron rod for corner from which new BTs  
were made as follows:  
W.Oak, 24" dia. bears N.30°E., 34.0 ft.  
Laurel, 4" dia. bears N.87°E., 158.5 ft.  
B.Oak, 6" dia. bears S.2°E., 41.5 ft.  
W.Oak 18" dia. bears N.1°W., 146.0 ft.

James W. Byron; Milo Godfrey; S. Bilow - June 23, 1959  
C.S. File 49/62-2

-----  
Found - ¾" Bolt at corner & 2 BTs set by Crocker.  
6" B.Oak, now 10", S.2°E., 41.5 ft. showing good  
scar, did not open.  
18" W.Oak, now 24", N.1°W., 146.0 ft. showing good  
scar, did not open.  
Clump of Laurels bears N.87°E., 158.5 ft., did not  
find one mkd. BT.  
New BTs - 9" W.Oak, N.84°E., 42.0 ft. blaze & scribe "T27S  
R.5W S30 CS BT".  
10" B.Oak, S.41½°W., 95.4 ft. blaze & scribe "T27S  
R6W S36 CS BT"

July, 1971 - ¾" Bolt missing, Set 5/8" I.Rod - Don Garrett  
See Map # M 42 - 50.

Cont. to page 2

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; 30 & 31, T 27-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Burton Holt - For: Mel Mendenhall - March 1981 - M 79 - 75 ----- CONDITION REPORT ONLY Found - A 2" x 2" angle iron fence post 5 ft. tall set in           concrete - 4 way fence junction (no record).           14" B.Oak bears S.43°W., 95.4 ft.           12" W.Oak beaaars N.84°E., 42.0 ft. The 5/8" iron rod set per M 42-50 (Garrett) is missing. Corner used as tie for M 79-75.</p>
<p>Found OK, August, 1990 - M 112 - 12</p>
<p>Found OK by B. Shaner, Nov. 1997 - 1998-0022 A &amp; B Found OK by R. Quimby, Jan. 2001 - M136-57</p>