

TOWNSHIP 27 RANGE 06 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7 of T27-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set 1/4 post, from which

A G.Oak, 36" dia. bears N.23 $\frac{3}{4}$ °E., 419 lks. dist.

A G.Oak, 20" dia. bears S.71°W., 131 lks. dist.

Ben. B. Irving - N.E. Richardson; Ernest Brown
S.E.R.A. project - 1934 - Volume 4 Pages 50-58

Set by proportional measurement by driving machine gun
barrel 10" underground, tin collar, one brick on top
three bricks placed around, 4"x4"x48" post, 24" in the
ground, mkd. $\frac{1}{4}$ S on North face, C.S. on South face, S. 7
on East face and S.12 on West face, from which

N.E. Corner D.L.C. No. 37 T.27S R5W bears N.75°12'E.,
924.9 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 4/93 - C.S. File 64/43-32

Corner looked for and not found.