

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Huntley DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Survey by J.A. Burnett, under Contract dated June 8, 1857 ----- Set a post marked as per instructions, from which A W.oak 24" dia., bears S.72°30'E., 224 lks.</p>
<p>W. F. Briggs, for: O.H. Buell - Aug. 25, 1894 - Volume 2 Page 7; Field Book 98 Page 33 ----- Set post marked C.L. 38 C.S. as per original witness tree still standing to wit: W.Oak 24" dia., bears N.72½°W., 224 lks. marked Cl. 38 C.S. BT.</p>
<p>J.W. Cole, for: Montgomery - 1915 - Vol. 2 Page 208-09; Field Book 37 Pages 6 & 8-12; and "old" corner book, Page 96 ----- Renew corner with Oak stake from which original tree bears S.72°30'E., 2.24 chs.</p>
<p>GL0 survey by Fred Mensch dated 1924 (DCSO records, Vol. 14 Page 5862) ----- Intersect NW. cor. of claim No. 38, designated by me as Cor. #2, which has been restored by county survey and is a steel plow point driven in ground; from which new bearing trees: A Laurel 9" dia., bears S.25¼°E., 97 lks. dist. marked A P 2 D L C 38 B T. A B.Oak 16" dia., bears S.74½°E., 160 lks. dist. marked A P 2 D L C 38 B T. Orig. bearing tree, a W.Oak 30" dia., bears S.72½°E., 224 lks. dist., old blaze visible.</p>
<p>Doug. County Surveyors Office - John M. Powell and F. Jones Feb. 1, 1968 - C.S. File 49/79-93 ----- Found - No trace of Plow Point as recorded in Vol. 2 Pg. 7 (Note: I found no mention of a "plow point" in either Vol. 2 Page 7 or Briggs field book 98. VL, 8/19/1992) 9" Laurel, now fragmentized, S.25°E., 64.0 ft., scribe found. 16" now 23" B.Oak S.74½°E. 105.6 ft. tree previously opened, scribe visible. Set Brass cap at NW Cor. DLC #38, County Surveyor's Office T 27 S R 7 W N.W. Cor DLC 38 1968 continued next page</p>

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Huntley DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 14" B.Oak S.28°E., 85.6 ft. mkd. N.W. DLC #38 CSBT SE BT OK and tagged.
Found OK by George Grubb, March 1982, M 91-62
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/18/2002 - C.S. File 66/48-9A&B ----- Found - 1968 DCS0 brass cap iron bent 2" below ground. 24" now 36" dia., 2½ ft. high W.Oak shell of stump bears S.70½°E., 149.5 ft. (Rec. S.72½°E., 147.8 ft.) OBT 16" now 24" dia., B.Oak with a previously opened fully healed blaze bears S.73°E., 105.6 ft. (Rec. S.74½°E., 105.6 ft.) 1924 14" B.Oak now 20" dia., W.Oak with a fully healed double blaze, bears S.27°E., 85.6 ft. (rec. S.28°E., 85.6 ft.) 1968 Fence corner with fence lines running E + S bears N.50°E., 8 ft. Straighten 1968 BC/IP and set at plumb position flush with ground. New - 17" dia., W.Oak double blazed & scribed "NW DLC 38 CS BT" bears S.8°E., 11.3 ft. (Note: BT in South fence line) SE Corner of gabled barn bears S.71½°W., 72.3 ft. Compass decl. 17½°E.