TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 048020

PRIMARY CORNER DESCRIPTION NW Cor. Wm. Morin DLC #48

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by J.A. Burnett, under Contract dated June 8, 1857

Set a post, from which
A W.Oak 36" dia., bears S.83½°E., 804 lks.

F.J. Cole, for: Seeley, Taylor, etal - July 1914, Field Book 39 Pages 47-48; Vol. 2 Page 179 and "old" corner book, Page 96

Renew corner with an Oak stake marked C.S. C.48 from which
Orig. BT bears S.83¼°E., 804 lks.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/16/2002 - C.S. File 66/34-35

Found - 36" now 36" dia., 2½ ft. high rotted W.Oak stump. We open & find rotted blaze, axe marks & scribing "T" bears S.83½°E., 530.6 ft. OBT (Note: bearing S.83½°E., taken from fiche copy of hand written DLC line notes)

Set - 2½" dia., brass cap on a 1½" O.D. by 32" long iron pipe at position determined from OBT. Protrudes 6" above ground. DOUGLAS CO. SURVEYORS OFFICE
T27S
R 7W
|NW
|DLC
|48
2002

17" dia., D.Fir double blazed & scribed "NW DLC 48 CS BT" bears S.59°W., 6.5 ft.

9" dia., W.Oak double blazed & scribed "NW DLC 48 CS BT" bears N.44°W., 33.1 ft.

18" dia., D.Fir single blazed & scribed "NW DLC 48 CS BT" bears S.58½°E., 21.0 ft.

7" dia., D.Fir double blazed & scribed "NW DLC 48 CS BT" bears N.83°E., 62.3 ft.

Corner lies approx. 55 ft. south of southerly edge of pond.

Compass decl. 17½°E.

GPS taken S.45°E., 100 ft. from BC/IP