

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by J.A. Burnett, under Contract dated June 8, 1857

Set a post from which
 A yellow Pine 24" dia., bears N.45°W., 104 lks. dist.

F.J. Cole, for: Seeley, Taylor and etal - July 1914
Field Book 39 Pages 47-48; Vol. 2 Page 179; and "old"
Corner book, page 96

Renew corner se rock from which Orig. witness tree:
 A Pine 24" dia., bears N.45°W., 104 lks.
(See also, Field Book 66 Page 24)

L.G. Hicks - 1914 - M 33-41 - C.S. File 19/30 A & B

Calls for a - 2"x6"x12" Sandstone
 30" Pine, N.46°W., 68.5'
 8" W. Oak, N.79½°W., 30.1'

Frear; J.H. Wolford; P.D. Wolford; Carl Richmond, Oct. 5, 1935
(I could find no record source for this renewal - see "old"
corner book, Page 98)

I set the corner by driving a 1" x 36" iron pin from which
the following trees bear
 A Forked W.Oak 12" dia. bears N.77½°W., 28.6 ft.
 A Locust 10" dia., bears N.40½°E., 5.8 ft.

Doug. County Surveyors Office - Rod Kimberling, Deputy -
P.L. Earle; F.C. Silagy - April 18, 1978 - C.S. File 59/46-84

Found - A 1" Iron rod at SE wire fence corner, bears
 S.77°W., 1.9 ft. from corner.
 A 30" Pine stump badly rotted, bears N.42½°W., (Rec
 N.46°W.) 68.5 ft. (M 33-41)
 An 8" now 23" W.Oak, measured below fork, bears
 N.79½°W., 30.1 ft. with "CSC 48" carved in a
 partly healed single blaze.
 A 10" Locust, measured South fork, bears N.26°E.,
 4.9 ft. with "SC 48 B" carved in a partly
 healed single blaze.
I set a 1" x 36" I.P. with a brass cap, set 5" above ground &
marked: "Douglas County Surveyor" T 27 S R & W
 1978 S.E. Ext |
 DLC 48 |

No new accessories.