

PRIMARY CORNER DESCRIPTION Interior L. Cor. Morin DLC #48

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by J.A. Burnett, under Contract dated June 8, 1857  
-----

Set a post, from which  
A W.Oak 10" dia., bears S.27°30'W., 55 lks.

L.G. Hicks - May 1914 - M 33-41 - C.S. 19/30 A & B - F.B. 66  
Pages 12 - 33  
-----

Found - 4" Oak post  
18" W.Oak, S.27½°W., 36.3'.  
Marked - 10" W.Oak, N.24°W., 25.8'.  
10" B.Oak, N.26°E., 29.5'.

F.J. Cole, for: Seeley; Taylor and et al - July 1914  
Field Book 39 Pages 47-48; Vol. 2 Page 179; and "old"  
Corner book, Page 96  
-----

Renew corner with Laurel post marked C.S. C.48, from which  
Orig. tree, a W.Oak 10" dia., bears S.27°30'W., 55 lks.

Doug. County Surveyors Office - Vernon Tracy and crew  
Dec. 6, 1968 - C.S. File 54/23-29  
-----

Found - Orig. 10" now 20" W.Oak, alive, S.27½°W., 36.3 ft.  
previously opened, scribe marks in very poor  
condition, visible.  
Find hole for Hick's NW BT and no trace of NE BT due  
to road.

Set Brass cap at cor. mkd: County Surveyor's T 27 S R 7 W  
Office, 1968 Int. L. DLC |48  
New BTs - 10" D.Fir N.33½°W., 69.9 ft. mkd: "Int. L DLC  
48 CS BT.  
8" D.Fir S.43°W., 54.0 ft. mkd: "Int. L DLC 48  
CS BT.  
This corner lies 60 ft. E. of Co. Rd., course NE-SW., See  
M 33-41

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 1/21/1999 - C.S. File 66/8-3  
-----

Found: 2½" brass cap on a 1½" o.d. iron pipe, protrudes  
11" above ground. 1968  
10" now 20" dia. 3 ft. high W.Oak stump with a  
partially opened blaze and axe marks visible,  
bears S.27½°W., 36.3 ft. OBT

(Cont. next page)

PRIMARY CORNER DESCRIPTION Interior L. Cor. DLC 48

Alias	Description

8" now 15" dia. D.Fir with a fully healed double blaze, bears S.43°W., 54.0 ft. 1968  
10" now 11" dia. D.Fir with a fully healed double blaze, bears N.33½°E., 69.9 ft. 1968. BT looks as if it may die.  
Oak remains found at record "N.24°W., 25.8 ft." 1914  
NEW: 15" dia. Pine double blazed and scribed "INT L DLC 48 CS BT" bears S.9°E., 7.7 ft.  
13" dia. W.Oak double blazed and scribed "INT L DLC 48 CS BT", bears N.20°W., 26.2 ft.  
Corner lies approx. 75 ft. east of county road.

---

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 9/21/2006 - C.S. File 67/14-26  
-----

Found - Monument as per 1999 renewal.  
15" now 20" dia., D.Fir, fully healed double blaze visible, bears S.43°W., 54.0 ft. agrees w/rec. 1968 BT.  
15" now 16" dia., Pine, mostly healed double blaze, visible bears S.9°E. 7.7 ft agrees w/rec. 1999 BT  
13" now 14" dia., W.Oak, healed double blaze visible bears N.20°W., 26.3 ft. agrees w/rec. 1999 BT  
20" dia., W.Oak stump is as fd. in 1999 ren. OBT  
11" D.Fir, now 11" dia., stump cut flush w/ground, bears N.33½°E., 69.9 ft. Agrees w/rec. 1968 BT.

New - 9" dia., W.Oak, double blazed & scribed "INT L DLC 48 CS BT" on high & low blazes, bears N.45½°E., 69.0 ft.

Note - Lies in small hillside horse pasture on gentle NW facing slope.  
Compass decl. 16½°E.