

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 052040

PRIMARY CORNER DESCRIPTION SSE Cor. Flourney DLC #52

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by J.A. Burnett, under Contract dated June 8, 1857

Set a post, from which
A B.Oak 12" dia., bears N.65°W., 37 lks.

Irving and Richardson - 1929 - C.S. File 22/39

Set 2 x 18" Iron pipe for corner by running in from NW corner of Cl. 53, East and Int. L corner of Cl. 52 and running South intersected, I set corner.
I marked the following tree:
Fir 14" dia., bears N.55°W., 48 lks. marked C.S. Cl. 52 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/11/1999 - C.S. File 66/16-5

Found - 3/4" I.D. iron pipe protrudes 7" above ground. (Per 1929 - 2" iron pipe)
14" now 19" dia., 3 ft. high rotted D.Fir stump, scribing found "BT" bears N.55°W., 31.7 ft. (agrees w/rec) 1929
New BTs - 13" dia., Madrone, double blazed & scribed "SSE DLC 52 CS BT" bears N.65½°W., 12.6 ft.
7" dia., B.Oak, double blazed & scribed "SSE DLC 52 CS BT" bears N.42°E., 14.2 ft.
9" dia., D.Fir double blazed & scribed "SSE DLC 52 CS BT" bears S.61°E., 14.0 ft.
12" dia. Madrone, double blazed & scribed "SSE DLC 52 CS BT" bears S.54°W., 31.5 ft.

Fd. Ok by Neil Hibbs, 8/2006 - M146-72