

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 052060

PRIMARY CORNER DESCRIPTION SE Cor. of Flourney DLC #52

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by J.A. Burnett, under Contract dated June 8, 1857

Set a post, from which
A W.Oak 16" dia., bears N.69°W., 89 lks.

B.B. Irving; N.E. Richardson; N. Conn - Oct. 10, 1938
C.S. File 22/39 - and 15/11

Set 3/4" x 40" Pipe 30" in ground in mound of rock 24" dia.,
and 12" high. Boulder 30" x 48" x 14" high bears S.65°W.,
5 ft. with X and B.O. chiseled on surface. Location
identified by distance from Int. L. Corner and hole where Oak
tree had burned out for location of O.B.T.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/16/1999 - C.S. File 66/16-9

Found - 3/4" I.D. iron pipe is found bent & broken, portion
of IP that would have protruded above ground is
approx. 11". 1938

No accessories found, area around corner has been
scraped in past by a bull dozer.

New BTs - 7" D.Fir double blazed & scribed "SE DLC 52 CS BT"
bears North 95.4 ft.

17" D.Fir single blazed & scribed "SE DLC 52 CS BT"
bears S.61°E., 58.3 ft.

4" B.Oak double blazed & scribed "X CS BT" bears
S.33°W., 39.8 ft.

4" W.Oak double blazed & scribed "X CS BT" bears
N.33½°W., 73.8 ft.

4'x2½'x2½' high stone we marked with an "X" on top,
X bears S.11°W., 40.5 ft. 5" X near top center.

Fd. Ok by Neil Hibbs, 8/2006 - M146-72