

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 054020

PRIMARY CORNER DESCRIPTION NNW Cor. Flourney DLC #54

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by J.A. Burnett, under Contract dated June 8, 1857

Set a post, from which
A W.Oak 14" dia., bears S.35°E., 120 lks.

Doug. County Surveyors Office - James Byron, Deputy
M. Godfrey; S. Bilow - April 24, 1958 - C.S. File 49/79-52

Found - Orig. 14" now 40" W.Oak S.35°E., 79.2 ft. I find
good scribing, "C 54 27S 8W BT" on old open
face. I find this BT was 24" when scribed not
14" as recorded. Checks good for ring count.
Old E.W. fence South 12.5 ft. New E.W. fence South 25.6 ft.
Set Brass cap at cor. mkd: N.W. Corner D.L.C. 54, T27S R7W
County Surveyor's Office, 1958
New BTs - 8" Cedar bears N.26°W., 4.0' scribed NW Cl 54 CS BT.
14" R.Fir bears S.42°W., 18.2 ft. scribed NW CL
54 CS BT.

Found OK, Aug. 1996 by D.Edwards - M 125-71

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/26/1999 - C.S. File 66/8-6

Found: 2½" brass cap on a 1½" o.d. iron pipe, protrudes
10" above ground, 1958
OBTs not found.
8" now 11" dia. Cedar with a fully healed double
blaze, bears N.26°W., 4.0 ft. 1958
14" now 19" dia. D.Fir with a fully healed double
blaze, bears S.42°W., 18.2 ft. 1958
NEW: 8" dia. W.Oak double blazed and scribed "NW DLC 54
CS BT" bears S.84°E., 3.5 ft.
9" dia. B.Oak double blazed and scribed "NW DLC 54
CS BT" bears N.67°W., 44.7 ft.
Corner lies near top of south bank of small gully that runs
S.65°E., approx. 10 ft. south of bottom.