

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 054050

PRIMARY CORNER DESCRIPTION SW Cor. Elerno's DLC #54

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - J.A. Burnett, Deputy, under contract dated June 8, 1857</p> <p>-----</p> <p>Set a post, from which A B.Oak 12" dia., bears N.21°E., 344 lks. dist.</p>
<p>H.L. Eppstein, Co. Surveyor - Wit. B.A. Lane; Bob Mathews; Fritzpatrick Bros. - June 30, 1930 - M 1-73; C.S. File 14/44 C.S. File 14/59</p> <p>-----</p> <p>I set from old BT. Set 4 x 4 x 36" Cedar post for corner and marked for new witness tree: A W.Oak 10" dia., bears N.55°E., 28.5 ft.</p>
<p>Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow - April 24, 1958 - C.S. File 49/79</p> <p>-----</p> <p>Found - Cole's BT, N.55°E., 28.4 ft. now 20" W.Oak. I open &amp; find good scribing marks. Set Brass cap at cor. mkd: S.W Cor DLC 54 T27S R7W County Surveyor's Office, 1958. New BT - I rescribe Cole's BT, 20" W.Oak N.55°E., 28.4 ft.: S W CL 54 CS BT. 6" B.Oak bears S.85°E., 13.3 ft scribed SW CL 54 CS BT</p>
<p>Found OK, Larry Dolan, May 1988, M 106-33 A&amp;B</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/31/2002 - C.S. File 66/34-44</p> <p>-----</p> <p>Found - 1958 DCS0 brass cap/iron pipe protrudes 13" out of ground. 12" B.Oak now depression in ground fd. at orig. rec. N.21°E., 227.0 ft. (OBT) 10" now 34" dia., W.Oak with a fully healed double blaze bears N.55°E., 28.5 ft. (1930) 6" now 24" dia., B.Oak with a fully healed double blaze bears S.85°E., 13.3 ft. (1958)</p> <p>New - 16" dia., D.Fir double blazed &amp; scribed "SW DLC 54 CS BT" bears N.43°E., 31.1 ft. Bonnevillle power 3½" brass cap on a 2" O.D. iron protrudes 5" out of ground bears East 109.6 ft. Corner lies 4½ ft. SW of a fence corner, fence line runs N + E. Compass decl. 17½°E.</p>
<p>Fd. BC by A Silbernagel - 05/2018 - M174-28 A-B</p>