

PRIMARY CORNER DESCRIPTION SW Cor. Section 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5226)

-----  
Set post, for Tp. 27 S., and ranges 7 and 8 west, from which:  
A B.Oak 15" dia., bears N.67°E., 56 lks. dist.  
A W.Oak 18" dia., bears N.40°W., 129 lks. dist.  
Cor. of Tp. 27 S., R. 7 and 8 West, established by Ford, bears North 878 lks. and East 1482 lks.

GL0 survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5277 and Page 5285)

-----  
(Page 5277)  
At the established SE. Cor. of T27S R8W, which cor. I restore from the original witness trees still standing to wit:  
A B.Oak 15" dia., bears N.67°E., 56 lks. dist. mkd. T27S R7W S31 BT.  
A W.Oak 18" dia., now dead, bears N.40°W., 129 lks. dist. mkd. T27S R8W S36 BT.  
By setting a post 3 ft. long, 4" sq., 24" in the ground for standard cor. of Tp. 27 S Rs 7 and 8 W marked SC T27S on N.; R7W S31 on E.; R8W S36 on W. faces, with 6 grooves on N., E., and W. faces, from which the original witness trees above described bear as heretofore recited and agreeing with description furnished by the Surveyor General, except the B.Oak, which is not 24". The marking upon it is plainly visible after removing the new growth of wood. The marking on the W.Oak is plainly visible. These trees were marked 41 years ago.  
This cor. is 8.99 chs. W. from the standard NE. cor. of T28S R8W.

(Page 5285)  
I begin at the Std. cor. for T27S Rs. 7 and 8 W. which is a post mkd. as described by the Examiner, to wit: T27S R8W S36 on W.; SC T27S R8W on N.; T27S R7W on E. faces, with 6 grooves on E. and W. faces. Witness trees correspond in brg. & dist. with original notes. I erase redundant markings on post and mark with 6 grooves on N. face to correspond with the notes thereof on file in the U.S. Surveyor General's office. viz: S C T27S on N.; R7W S31 on E.; R8W S36 on W. faces, with 6 grooves on NE. and W. faces.

(Cont. Next Page)

