

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. 30 & 31; 25 & 36 of T 27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5226)

Set post, cor. secs. 30, 31, 25 and 36, from which
A Laurel 20" dia., bears N.56°W., 6 lks. dist.
A Laurel 10" dia., bears N.1¼°E., 100 lks. dist.
A Fir 36" dia., bears S.18°E., 43 lks. dist.
A Fir 36" dia., bears S.12°W., 57 lks. dist.

H.C. Brown, Deputy Co. Surveyor, for C.H. Allen, 1906
Volume 2 Page 142

Found stake rotted off, Witness trees, and set new stake.

H.L. Eppstein, Co. Surveyor - June 30, 1930 - For:
Fritzpatrick's Bros. - M 1-73; C.S. 14/44; C.S. 14/59 and "old"
corner book, Page 97

Set corner from three old witness trees. I set 4 x 4 x 36"
Yew wood post for corner. The tree old trees being in good
shape, I only marked new BT in section 30 as follows:
Red Fir 20" dia., bears N.28°E., 45.0 ft.

Doug. County Surveyors Office - James W. Byron, Deputy
M. Godfrey; S. Bilow - April 23, 1958 - C.S. File 49/79-47

Found - All four BTs as recorded in 1930 renewal.
The NE, SE, and SW BTs now stumps, show good scars.
I open NE BT, shows good scribing.
The 20" Laurel, now 24" snag, N.82°W., 4.0 ft.,
record N.56°W., 4.0 ft. Has open face with good
scribing.

All BTs check bearings & distances except Laurel for bearing.
Set Brass cap at cor mkd: County Surveyors Office S25|S30
1958 T27S R8W S36|S31 R7W

New BTs - 50" R.Fir bears N.81°W., 23.3 ft. scribed S25 T27S
R8W CS BT.
58" Cedar bears N.24½°E., 351.0 ft. scribed S30
T27S R7W CS BT.

continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. 30 & 31; 25 & 36 of T. 27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tony Hostetter - For: Weyerhaeuser Co. - July 2001 - M138-66
(See also undated WEYCO visit C.S. file 58/271-9)

-
- Found - 1½" iron pipe w/brass cap set by DCS0, 1958 CS 49/79
36" Fir stump, no marks visible OBT, bears
S.11°45'E., 28.9 ft.
54" Fir stump, 1958 BT, face evident, bears
N.81°33'W., 22.4 ft.
60" Cedar, face evident, tagged bears (N.24°30'E.,
351.0 ft) not measured.
- New BT - 16" Fir, scribed "S 30 SW BT" bears N.50°41'E., 23.2
ft. to spike. Measured to the head of 6" spike.
BT tag.
16" Fir scribed "S 31 NW BT" bears S.51°E. 7.4 ft to
spike. Measured to the head of 6" spike. BT tag.
8" Madrone, scribed "S 25 SE BT" bears N.15°59'W.,
17.4 ft to spike. Measured to the head of 6"
spike. BT tag.

Fd. Ok by Tony Hostetter - For: Seneca Jones Timber Co. -
Aug. 2002 - M140-72