

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T27-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 12 Page 5228)

Set post cor. secs. 18, 19, 13 and 24, from which
A Hemlock 5" dia., bears N.31°W., 13 lks. dist.
A Hemlock 3" dia., bears N.40°E., 7 lks. dist.
A Hemlock 8" dia., bears S.37°W., 26 lks. dist.
A Hemlock 6" dia., bears S.60°E., 2 lks. dist.

Original - A.R. & L.C. Flint, under Contract #392 dated May 26, 1881 - (DCSO records, Vol. 13 Pages 5268)

Cor. to secs. 18, 19, 13, & 24. Made & set a new Cedar post - old witness trees, all found which were as follows:
Hemlock 5" dia., bears N.31°W., 13 lks. dist.
Hemlock 3" dia., bears N.40°E., 7 lks. dist.
Hemlock 8" dia., bears S.37°W., 26 lks. dist.
Hemlock 6" dia., bears S.60°E., 2 lks. dist.

Douglas Co. Surveyors Office - Gregory E. Quibell, John Powell - May 6, 1982 - C.S. 58/271-2 (also see 58/271-8)

CONDITION REPORT ONLY

Found - Unrecorded 3/4" x 30" I.P. loosely set, protruding 12" out of ground.
36" Fir stump with "W" nail & Weyerhaeuser BT tag, bears N.39°E., 16.2 ft.
19" Fir stump with "W" nail & Weyerhaeuser BT tag, bears S.32°E., 12.2 ft.
12" Hemlock stump with "W" nail & Weyerhaeuser BT tag, bears N.40°W., 8.6 ft. This is possibly an orig. BT, however, there is no face or scribing visible.
33" Fir stump with "W" nail & Weyerhaeuser BT tag, bears S.82°W., 13.4 ft.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-7

Per note on file:

"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - DCSO
The following information is on Weyerhaeuser Co. paper:
continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

3/4"x30" IP standing loosely, from which
24" fir stump, N.49°E., 16.2 ft (penciled in: 36"
N.39°E., & "W" nail tag)
(penciled in: 19" Fir stump S.32°E., 12.2 "W" nail tag)
(penciled in: 12" Hemlock N.40°W., 8.6 "W" nail tag.)
(penciled in: 33" Fir S.82°W., 13.4 "W" nail tag)
I believe the penciled in info is by GQ, DCSO: JC - DCSO