

PRIMARY CORNER DESCRIPTION Tsp. Cor. NW Cor. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 11 Page 4592)

Set post cor. of tps. 26 and 27 south, Rgs. 7 & 8 West, from which:

- A Fir 36" dia., bears N.40°W., 93 lks. dist.
- A Fir 24" dia., bears S.32°W., 83 lks. dist.
- A Fir 36" dia., bears S.50°E., 4 lks. dist.
- A Cedar 18" dia., bears N.20°E., 102 lks. dist

Fd. by GLO surveyors Flint & Flint in 1881, (DCSO records, Vol. 11 Pg. 4621 and 4641)

GLO survey by William P. Heydon, Deputy, under Contract #656, dated May 21, 1896 (DCSO records, Vol. 11 Page 4649)

At the cor. of Tps. 26 and 27 S., Rs. 7 & 8 W., which is a badly decayed fir post. I set a new fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of Tps. mkd. T26S S31 on NE., R7W S6 on SE., T27S S1 on SW and R8W S36 on NW faces; with 6 notches on each edge. From which the original witness trees:

- A Cedar 24" dia., (given in Surveyor Generals notes as 18" dia.) bears N.20°E., 102 lks. dist. (marks overgrown)
- A Fir 36" dia., (now dead) bears S.50°E., 4 lks. dist. marks indistinct.
- A Fir 24" dia., bears S.32°W. 83 lks. mkd. T27S R8W S1 BT
- A Fir 36" dia., bears N.40°W., 93 lks. dist., mkd. T27S R8W S36 BT.

Shaner Engineering - For: Hub Lbr. and Weyerhaeuser Co. M 49-49 - Dec. 21, 1973

Found - 40" D.Fir stump, orig. BT, face badly burned, scribes visible, bears S.32°W., 54.8 ft.
36" D.Fir stump, probably orig. BT, badly burned & rotted, bears N.35°W., 59.0 ft. (Rec. N.40°W., 61.4 ft.)
36" Cedar stump, prob. orig. BT. I rescribed T26S R7W S31 BT, bears N.20°E., 78.0 ft. (Rec.67.3')
Set Brass cap mkd. T26S R8W S36; T26S R7W S31; T27S R8W S1; T27S R7W S6.
New BTs - 6" D.Fir scribed T26S R8W S36 BT, bears N.64°W., 55.4 ft.
8" Hemlock scribed T27S R7W S6 BT, bears S.62°E., 24.7 ft
8" D.Fir scribed T27S R8W S1 BT, bears S.34°W. 114.4 ft

Cont.

PRIMARY CORNER DESCRIPTION Tps. Cor. NW Cor. Sec. 6

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM dependent resurvey, by Peterson; Popken; Berry & Wofford, Group #744 and 838, dated May 1971 and 1974. (DCSO records, Volume 37 Pages 15161-62)

 The cor. of Tps. 26 and 27 S., Rs. 7 & 8 W., perpetuated & recorded by Bruce Shaner Registered Logging Engineer #4906, in 1973, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap mkd.

T 26 S
 R 8 W R 7 W
 S 36 | S 31
 S 1 | S 6
 T 27 S
 1973

from which the remains of the original bearing trees
 A sawed cedar stump, 36" dia., bears N.20°E., 118 lks. dist., with scribe marks T26S R7W S31 BT. visible on open blaze. This tree was rescribed by Shaner. (Record, 102 lks.)
 A sawed fir stump 40" dia., bears S.32°W., 83 lks. dist. with scribe marks BT visible on burned blaze.
 A sawed fir stump, 36" dia., bears N.33½°W., 89 lks. dist., no marks visible (Record, N.40°W., 93 lks.)
 and bearing trees mkd. by Shaner
 A Hemlock 7" dia., bears S.55°E., 37½ lks. dist., with scribe marks T27S R7W S6 BT visible on open blaze.
 A Fir 8" dia., bears S.35°W., 173½ lks. dist., with scribe marks T27S R8W S1 BT visible on open blaze.
 A Fir 6" dia., bears N.64°W., 84 lks. dist., with scribe marks T26S R8W S36 BT visible on open blaze.
 and a new bearing tree
 A hemlock 8" dia., bears N.22°E., 148 lks. dist. mkd. T26S R7W S31 BT.

Found OK by T. Hostetter, Nov. 1999 - M134-63

Tony Hostetter - For: Weyerhaeuser Co. Co. - March 2010 - C.S. File 65/69-13

 Found - 1973 brass cap as described by Shaner (M49-49)
 46" Fir stump, BLM tag, bears N.20°E., 78.0 ft.
 22" Hemlock, face evident, BLM tag, bears N.22°E., 97.7 ft.
 24" Hemlock, face evident, BLM tag, bears S.62°E., 24.7 ft.
 42" Fir stump, scribing visible bears S.32°W., 54.8 ft. continued next page

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New BTs- 14" Fir, Weyco tag & spike, bears S.60°W., 10.0 ft.
to spike.
15" Fir, Weyco tag & spike, bears N.25°W., 18.4 ft.
to spike.